

API Reference

- [Overview](#)
- [Binary Objects](#)
- [Data Actions](#)
- [Admin Actions](#)
- [Task and Thread Actions](#)
- [Struct Actions](#)
- [Specifier Syntax](#)
- [Record Syntax](#)
- [Expression Syntax](#)
- [Select Syntax](#)
- [Definitions Syntax](#)
- [Action Index](#)

Overview

The **XINA API** (or **XAPI**) provides programmatic access to a XINA server.

Note that client applications do not connect directly to the server. The [XINA Tunnel](#) utility performs the actual server connection, authentication, and security, and provides a local server for local client to connect.

XAPI is built on the **XINA Protocol** (or **XProtocol**), a TCP format used to communicate with the XINA server. It is designed to be simple and easy to implement across many languages and environments, using standard UTF-8 character encoding and JSON data structures.

Tokens

XProtocol is intended to be parsed in-place as a stream is read. This is achieved with variable length **tokens** of the following format:

- prefix length: one byte UTF-8 digit indicating length of the prefix in bytes
- prefix: UTF-8 digit(s) indicating the length of the content in bytes
- content: UTF-8 encoded string or binary data of (prefix count) bytes

For example:

- 14cake = "cake"
- 213big hamburger = "big hamburger"

The maximum allowed length of a single token is 2GB. A token may also be empty, which can be denoted with either the prefix 10 or the shorthand prefix 0.

Note that the content length is specified in *bytes*, not *characters*. Because UTF-8 is a variable length encoding format, it is recommend to first convert string data to bytes before creating a token for an accurate count.

Packets

Tokens are combined together into **packets**, which form all communication between the client and server.

Client Packets

Client packets are sent from the client to server. They use the following format:

- packet type :: one byte UTF-8 character
- header token :: JSON object containing header information (used primarily for system purposes, typically empty)
- content token :: UTF-8 encoded JSON object, binary data, or empty depending on token type

Client packets use the following packet types:

| Type | Code | Description |
|-----------|------|--|
| ACTION | A | contains an API action (most common packet type) |
| BINARY | B | contains binary data (used for transmitting file data) |
| CLOSE | X | closes the connection |
| CONTINUE | C | prompts continuing a data stream from the server |
| END | E | indicates the end of a series of binary packets |
| INIT | I | initializes the connection |
| KEEPALIVE | K | ignored by both server and client, keeps connection open |
| OBJECT | O | indicates the start of a binary object |

Server Packets

Server packets, inversely, are sent from the server to clients. They use the following format:

- packet type :: one byte UTF-8 character
- status code :: three byte UTF-8 numeric status code
- header token :: JSON object containing header information (only used currently for system functions, typically empty)
- status token :: JSON object containing status information
- content token :: UTF-8 encoded JSON object, binary data, or empty depending on token type

Server packets use the following packet types:

| Type | Code | Description |
|-----------|------|--|
| KEEPALIVE | K | ignored by both server and client, keeps connection open |
| SERVER | S | primary server packet type, used for all functions |

The server packet status token is a JSON object in the following format:

```
{
  "type"   : "OK" or "ER",
  "code"   : <int>,

```

```
"message" : <string, optional>
}
```

The `"type"` indicates if an action succeeded (`"OK"`) or failed (`"ER"`). The `"code"` is a numeric identifier for the status and will be in the range of 100 to 500.

| Code | Description |
|------|------------------------------|
| 1XX | Success, more data available |
| 2XX | Success, data ended |
| 4XX | Content error |
| 5XX | Server error |

The optional `"message"` contains a plain text description of the status or error.

Control Flow

In practice the general design of XProtocol is call and response. Each packet (of most types) sent by a client will receive a single server packet in response. The exception to this rule is the [binary object upload](#) procedure, detailed below.

Initialization

When an application opens a connection with the XINA Tunnel, it must first send a single `INIT` packet containing a JSON object:

```
{ "version": "3.0" }
```

Currently the only attribute for this object is the XProtocol version number, which is currently 3.0. More attributes may be added in the future. The XINA Tunnel will then respond with a server packet indicating if the initialization is accepted. If it is not, the connection will then be closed by XINA Tunnel. If it is accepted the application may then begin sending other XAPI packets.

Actions

The bulk of the XAPI communication consists of a collection of discrete **actions**. Actions are fully **transactional**; any changes performed by an action must **all** be successful or **no** changes will be committed.

Each action is encoded as a single JSON object, with the exact format dependent on the action type. There are two categories of actions; [data actions](#), which read or manipulate data, and [administrative actions](#), which alter data structures or perform other administrative tasks.

All actions have a standard server response. If an action returns no data (such as a write action), or if the returned data fits in a single `SERVER` packet, the server will respond with a single `SERVER` packet, indicating success or failure for the action in the status token, and with any returned data in the content token. If a `SERVER` packet contains data, it will always be formatted at a single JSON object.

| client | | server |
|--------|----|--------|
| ACTION | -> | |
| | <- | SERVER |

In some cases the server may send the results of a query over multiple packets. This is indicated by a 1XX status code in a SERVER packet. The client may send a CONTINUE token to receive the next packet, until a 2XX code is received, indicating the data has been sent.

| client | | server |
|----------|----|------------|
| ACTION | -> | |
| | <- | SERVER 1XX |
| CONTINUE | -> | |
| | <- | SERVER 1XX |
| CONTINUE | -> | |
| | <- | SERVER 2XX |

In this case, the complete data response can be aggregated from the JSON objects according to the following rules:

- properties appearing in a single object are included as-is
- properties appearing in multiple objects are merged based on the data type
 - if the first instance of a property is a JSON array, successive arrays are concatenated and non-arrays are appended
 - otherwise, the values are appended individually into a JSON array

For the purposes of this merge operation, an explicit null value should be included in merged results, whereas an explicit or implicit undefined should not.

Example

Given the following three server packets:

```
{
  "a": 0,
  "b": 1
}
```

```
{
  "a": undefined,
  "b": [2]
  "c": [4, 5, 6]
}
```

```
{
  "b": null,
  "c": [7, 8, 9]
}
```

The correctly merged result would be:

```
{
  "a": 0,
  "b": [1, [2], null],
  "c": [4, 5, 6, 7, 8, 9]
}
```

Binary Object Upload

The `OBJECT`, `BINARY`, and `END` packet types allow a client to upload binary objects (such as files) to XINA. Binary objects received by the server are assigned a unique ID, which is returned to the client. The client may then use the ID to refer to the cached object in a future action. Cached objects are deleted if not used within 24 hours.

| client | | server | notes |
|---------------------|--------------------|-------------------------|---|
| <code>OBJECT</code> | <code>-></code> | | initializes the object |
| <code>BINARY</code> | <code>-></code> | | contains binary data |
| <code>...</code> | <code>-></code> | | contains additional binary data as needed |
| <code>END</code> | <code>-></code> | | ends the object |
| | <code><-</code> | <code>SERVER 2XX</code> | content contains <code>object_id</code> |

The `SERVER` token content will be a JSON object in the format:

```
{ "object_id": "<id>" }
```

Unlike other packet types, the server will not respond to each client packet, but only once the `END` packet is received. If the client sends any packet other than an `END` or `BINARY` packet after an `OBJECT` or `BINARY` packet any loaded data will be discarded. If an `END` packet is received without any binary data, an `object_id` will not be returned.

Binary Objects

Binary objects are used to import any type of binary data. This may be used in conjunction with the low level API [upload function](#), or the data may be embedded directly.

Uploaded Objects

When referencing an uploaded binary object, the object is specified as a string by the server-provided `"object_id"`. The object must have been uploaded prior to the API action in which it is being referenced.

Example

```
{
  "file": "<object ID>"
}
```

Embedded Objects

Alternatively, the content of an object may be embedded directly in JSON API actions.

Text

A `text` binary object contains UTF-8 encoded plain text.

Example

```
{
  "file": {
    "type": "text",
    "content": "<plain text>"
  }
}
```

Base64

A `base64` binary object must be encoded with the [standard RFC 4648 format](#).

Example

```
{
  "file": {
```

```
"type": "base64",  
"content": "<base64 encoded text>"  
}  
}
```


Data Actions

Data actions read from or write to XINA databases.

Read Actions

SELECT

The primary read action in XINA. It closely mirrors the MySQL `SELECT` query, and returns data as a header of columns and list of rows. The full syntax for the `SELECT` object is available [here](#).

| Property | Value | Req | Default |
|-------------|----------|-----|---------|
| action | "select" | ? | |
| select | select | ? | |
| rows | integer | | 10,000 |
| use_strings | boolean | | false |
| echo | boolean | | false |

The server response to a `SELECT` action will start with a header packet, containing a JSON array of JSON object(s) indicating the `name` of each column as a `string` and the XINA data type of each column as a `string`. This will be followed by packet(s) containing the data, as a JSON array of of JSON array(s) of values.

The optional `rows` property sets the limit of rows per packet. Note that this *does not* limit the total number of rows returned, this is set by the `limit` property of the select object.

If the `use_strings` property is `true`, all values will be stored as JSON strings instead of their associated JSON type.

If the `echo` property is `true`, the generated SQL query will be included in the header object in the `"query"` property. This is provided to support query debugging; it does not affect the query itself.

Example

Given a table `t` with two columns, `a` (`int(4)`), and `b` (`utf8text`), and three rows:

| a | b |
|---|-----|
| 0 | "x" |
| 1 | "y" |
| 2 | "z" |

The following `SELECT` action:

```
{
  "action": "select",
  "select": {
    "from": "t"
  },
  "rows": 2
}
```

Would return three server packets.

First, the header information:

100

```
[
  {
    "name": "a",
    "type": "int(4)"
  },
  {
    "name": "b",
    "type": "utf8text"
  }
]
```

Second, the first two rows (limited to two by the `rows` property):

100

```
[
  [ 0, "x" ],
  [ 1, "y" ]
]
```

Third, the last remaining row (with the status code `200` indicating the end of the data):

200

```
[
  [ 2, "z" ]
]
```

FETCH

Reads specific types of data in a more structured format than the `SELECT` action. Although the syntax and response format differs depending on fetch type, all fetch actions share the boolean property `"count"`, which if true, overrides the default action output with a single value indicating the total count result for the current selection.

```
{
  "count": <integer>
}
```

FETCH RECORDS

Fetches records from a database.

| Property | Value | Req | Default |
|----------|----------------------|-----|------------------------|
| action | "fetch" | ? | |
| fetch | "records" | ? | |
| database | database specifier | ? | |
| records | records specifier | | |
| where | expression | | |
| order | array of order terms | | default database order |
| limit | integer | | 1,000 (see below) |
| offset | integer | | |
| children | boolean | | true |
| count | boolean | | false |

Fetches records are returned as JSON objects, with each attribute and field name as a property key with the corresponding value. In databases with the `file` feature enabled, each record will also include a generated presigned URL in the `"file_url"` property, and an S3 key reference in the `"file_key"` property.

If `children` is `true` and the specified database contains one or more child databases, all child records for each record will be included in the result. Each record with children will contain a `"children"` property, a JSON object with each key containing the name of the child database, and each value a JSON array of child record(s).

If both `records` and `where` are provided, they will be combined with a boolean `AND` operation.

The default limit for this operation is 1,000. Unlike the `SELECT` action which streams data directly from the underlying database, `FETCH` involves additional server overhead processing and formatting the result, so a limit is enforced to maintain system performance. Exceeding the default limit explicitly is permitted but may cause performance issues depending on server configuration.

FETCH MULTIRECORDS

Fetches records from several databases at once.

| Property | Value | Req | Default |
|-----------|--------------------------------------|-----|---------------------------------|
| action | <code>"fetch"</code> | ? | |
| fetch | <code>"multirecords"</code> | ? | |
| databases | databases specifier | ? | |
| where | expression | | |
| order | array of order terms | | default order of first database |
| limit | integer | | 1,000 (see below) |
| offset | integer | | |
| children | boolean | | <code>true</code> |
| count | boolean | | <code>false</code> |

Fetched records are returned as JSON objects, in the same format as the standard `FETCH RECORDS` action, with the same behavior for file and child records. Each top level record will also include a `"database_id"`, with the numeric database ID of the database of origin for the record.

Internally this action uses the multi-database source, which creates a SQL UNION of the record tables of each database as a single virtual table. This is achived by unioning each column by field name. As such this action works best with databases with the same set of fields (names and data types). If databases each have fields with the same names but different types unpredictable server or client side errors may result.

FETCH PSEUDORECORDS

Fetches data from an arbirary query formatted as though it represents a set of records.

| Property | Value | Req | Default |
|----------|--------------------------------------|-----|---------------------------------|
| action | <code>"fetch"</code> | ? | |
| fetch | <code>"pseudorecords"</code> | ? | |
| select | select | ? | |
| where | expression | | |
| order | array of order terms | | default order of first database |
| limit | integer | | |
| offset | integer | | |
| count | boolean | | <code>false</code> |

Each row of the result will be formatted as a JSON object, with each property key taken from the `SELECT` response header.

FETCH FOLLOW

Fetches all follows for a single user.

| Property | Value | Req | Default |
|----------|----------------------|-----|---------|
| action | <code>"fetch"</code> | ? | |

| Property | Value | Req | Default |
|----------|--------------------------------|-----|--------------------|
| fetch | <code>"follows"</code> | ? | |
| user | user specifier | | current user |
| count | boolean | | <code>false</code> |

FETCH KEYS

Fetches all keys for a single user.

| Property | Value | Req | Default |
|----------|--------------------------------|-----|--------------------|
| action | <code>"fetch"</code> | ? | |
| fetch | <code>"keys"</code> | ? | |
| user | user specifier | | current user |
| count | boolean | | <code>false</code> |

FETCH NOTIFICATIONS

Fetches notifications for a single user.

| Property | Value | Req | Default |
|----------|--------------------------------|-----|--------------|
| action | <code>"fetch"</code> | ? | |
| fetch | <code>"keys"</code> | ? | |
| user | user specifier | | current user |
| type | notification type | | |
| seen | boolean | | |

Notifications will always be returned ordered by time, descending.

If `type` is provided, only notifications of the same type will be returned.

If `seen` is `true`, only seen notifications will be returned. If `seen` is `false`, only unseen notifications will be returned.

FETCH POSTS

Fetches wall posts.

| Property | Value | Req | Default |
|-----------|--------------------------------|-----|--------------------|
| fetch | <code>"posts"</code> | ? | |
| wall | wall specifier | | all walls |
| following | boolean | | <code>false</code> |
| threads | boolean | | <code>false</code> |

| Property | Value | Req | Default |
|----------|---------|-----|---------|
| post | post ID | | |
| children | boolean | | false |
| records | boolean | | false |

FETCH PREFS

Fetches preferences for a single user.

| Property | Value | Req | Default |
|----------|----------------|-----|--------------|
| action | "fetch" | ? | |
| fetch | "prefs" | ? | |
| user | user specifier | | current user |

FETCH PREF DEFS

Fetches server preference definitions.

| Property | Value | Req | Default |
|----------|-------------|-----|---------|
| action | "fetch" | ? | |
| fetch | "pref_defs" | ? | |

FETCH USER SUBSCRIPTIONS

Fetches subscriptions for a single user.

| Property | Value | Req | Default |
|----------|----------------------|-----|--------------|
| action | "fetch" | ? | |
| fetch | "user_subscriptions" | ? | |
| user | user specifier | | current user |

FETCH TASKS

Fetches task information.

| Property | Value | Req | Default |
|----------|----------------|-----|---------|
| action | "fetch" | ? | |
| fetch | "tasks" | ? | |
| from | task ID | | |
| user | user specifier | | |
| text | string | | |
| where | expression | | |

| Property | Value | Req | Default |
|----------|--------------------------------------|-----|--------------------------|
| order | array of order terms | | recent first |
| limit | integer | | 1,000 (see below) |
| offset | integer | | |
| count | boolean | | <input type="checkbox"/> |

FETCH TEAM SUBSCRIPTIONS

Fetches subscriptions for a single team.

| Property | Value | Req | Default |
|----------|---|-----|---------|
| action | <input type="text" value="fetch"/> | ? | |
| fetch | <input type="text" value="user_subscriptions"/> | ? | |
| team | team specifier | ? | |

FETCH THREADS

Fetches all task threads.

| Property | Value | Required | Default |
|----------|--------------------------------------|----------|---------|
| action | <input type="text" value="fetch"/> | ? | |
| fetch | <input type="text" value="threads"/> | ? | |

FETCH USERS

Fetches user information.

| Property | Value | Req | Default |
|----------|--------------------------------------|-----|-------------------|
| action | <input type="text" value="fetch"/> | ? | |
| fetch | <input type="text" value="users"/> | ? | |
| users | users specifier | | all users |
| order | array of order terms | | recent first |
| limit | integer | | 1,000 (see below) |
| offset | integer | | |

DOWNLOAD

The download action generates a signed URL to download a file stored in the XINA system. Note that this does not actually perform the download; the returned URL can be used outside the XINA API to download the file.

DOWNLOAD RECORD

Generates a signed URL for a record file.

| Property | Value | Req | Default |
|----------|------------------------------------|-----|-------------|
| action | <code>"download"</code> | ? | |
| download | <code>"record"</code> | ? | |
| database | database specifier | ? | |
| record | record specifier | ? | |
| version | integer | | most recent |

DOWNLOAD POST

Generates a signed URL for a post file.

| Property | Value | Required | Default |
|----------|-------------------------|----------|---------|
| action | <code>"download"</code> | ? | |
| download | <code>"post"</code> | ? | |
| post | post ID | ? | |

Write Actions

INSERT

The INSERT action inserts one or more records into a XINA database.

By default, the action will fail if any records being inserted have duplicate key values already in the database. If a different `on_duplicate` property is set, duplicate records will be updated according to the rules in the table. Only fields explicitly set in the `INSERT` will be changed. This is analogous to an `INSERT ... ON DUPLICATE KEY UPDATE` MySQL query.

| Property | Value | Req | Default |
|--------------|--|-----|---------------------|
| action | <code>"insert"</code> | ? | |
| database | database specifier | ? | |
| records | records data | ? | |
| on_duplicate | <code>"fail"</code> or <code>"update"</code> | | <code>"fail"</code> |
| fail_no_op | <code>boolean</code> | | <code>false</code> |

Examples

Given a starting database containing key field `k`, fields `f1`, `f2`, and `f3`, with tags enabled, containing the following two records:

| k | f1 | f2 | f3 | tags |
|---|----|----|----|------|
| a | 1 | 2 | 3 | t1 |
| b | 1 | 2 | 3 | t1 |

And inserting records:

```
[
  { "k": "a", "f1": 4, "f2": null, "tags": ["t2"] },
  { "k": "c", "f1": 1, "f2": null, "tags": ["t2"] }
]
```

on_duplicate: "fail"

Action fails due to duplicate key value "a". No change occurs.

on_duplicate: "update"

Record with key value "a" is updated, and record with key value "c" is inserted. Note that field f3 of "a" is unaffected because no inserted records specified an explicit value for f3.

| k | f1 | f2 | f3 | tags |
|---|----|------|------|--------|
| a | 4 | null | 3 | t1, t2 |
| b | 1 | 2 | 3 | t1 |
| c | 1 | null | null | t2 |

REPLACE

The REPLACE action inserts one or more records into a XINA database and **overwrites** any existing records with duplicate keys.

| Property | Value | Req | Default |
|--------------|--|-----|----------|
| action | "replace" | ? | |
| database | database specifier | ? | |
| records | records data | ? | |
| on_duplicate | "update", "delete", or "trash" (if trash enabled for database) | | "update" |
| fail_no_op | boolean | | false |

Examples

Given a starting database containing key field k, fields f1, f2, and f3, with tags enabled, containing the following two records:

| k | f1 | f2 | f3 | tags |
|---|----|----|----|------|
| a | 1 | 2 | 3 | t1 |
| b | 1 | 2 | 3 | t1 |

And replacing records:

```
[
  { "k": "a", "f1": 4, "f2": null, "tags": ["t2"] },
  { "k": "c", "f1": 1, "f2": null, "tags": ["t2"] }
]
```

on_duplicate: "update"

Record with key value "a" is updated, and record with key value "c" is inserted. Note that f3 of "a" is now null and t1 is removed because all fields are overridden by the incoming record.

| k | f1 | f2 | f3 | tags |
|---|----|------|------|------|
| a | 4 | null | null | t2 |
| b | 1 | 2 | 3 | t1 |
| c | 1 | null | null | t2 |

on_duplicate: "trash" or "delete"

Existing record with key value "a" is deleted (or trashed), and new records "a" and "c" are inserted.

| k | f1 | f2 | f3 | tags |
|---|----|------|------|------|
| b | 1 | 2 | 3 | t1 |
| a | 4 | null | null | t2 |
| c | 1 | null | null | t2 |

If "trash" is used, the trash table now contains the original "a" record.

| k | f1 | f2 | f3 | tags |
|---|----|----|----|------|
| a | 1 | 2 | 3 | t1 |

SET

The SET action sets a database to contain the provided, and *only* the provided, records. Other records already present in the database are removed (either trashed or deleted, depending on the provided configuration).

| Property | Value | Req | Default |
|----------|-------|-----|---------|
| action | "set" | ? | |

| Property | Value | Req | Default |
|--------------|--|-----|--|
| database | database specifier | ? | |
| records | records data | ? | |
| on_duplicate | "update", "delete", or "trash" (if trash enabled for database) | | "update" |
| on_remove | "delete" or "trash" (if trash enabled for database) | | "trash" if enabled, "delete" otherwise |
| fail_no_op | boolean | | false |

Examples

Given a starting database containing key field `k`, fields `f1`, `f2`, and `f3`, with tags enabled, containing the following two records:

| k | f1 | f2 | f3 | tags |
|---|----|----|----|------|
| a | 1 | 2 | 3 | t1 |
| b | 1 | 2 | 3 | t1 |

And setting records:

```
[
  { "k": "a", "f1": 4, "f2": null, "tags": ["t2"] },
  { "k": "c", "f1": 1, "f2": null, "tags": ["t2"] }
]
```

on_duplicate: "update"

Record "a" is updated, record "c" is inserted, and record "b" is deleted (or trashed, depending on `on_remove`). Note that `f3` of "a" is now `null` and `t1` is removed because all fields are overridden by the incoming record.

| k | f1 | f2 | f3 | tags |
|---|----|------|------|------|
| a | 4 | null | null | t2 |
| c | 1 | null | null | t2 |

on_duplicate: "trash" or "delete"

All existing records are deleted (or trashed, depending on `on_remove`), and new records "a" and "c" are inserted.

| k | f1 | f2 | f3 | tags |
|---|----|------|------|------|
| a | 4 | null | null | t2 |
| c | 1 | null | null | t2 |

UPDATE

The UPDATE action updates the values of one or more fields and/or attached files of one or more records in a single database.

This documentation applies to XINA 9.2 and above.

| Property | Value | Req | Default |
|-------------|---|-----|---------|
| action | "update" | ? | |
| database | database specifier | ? | |
| records | records specifier | ? | |
| fields | jsonobject map of fields to values to update (see below) | | |
| expressions | jsonobject map of fields to expressions to update (see below) | | |
| file | string object ID of file to update (see below) | | |
| fail_no_op | boolean | | false |

The `fields` and `expressions` properties are JSON objects, where each key is interpreted as a [field specifier](#) in the context of the current database. For the `fields` property, each value is interpreted as a literal JSON value for the type of the specified field. For the `expressions` property, each value is interpreted as an [expression](#), with the evaluated result of the expression stored with the record. These are provided separately because expressions would otherwise not be distinguishable from JSON object value literals.

The `file` property may be provided for databases with the `file` feature enabled. When the file is updated, associated file record attributes (`file_size`, `file_type`, etc) will be updated automatically from the new file.

If a single field is referenced more than once across the `fields` and `expressions` object, the action will fail, as the result would be ambiguous.

By default, if no records are found matching the records specifier, or no values are provided for `fields`, `expressions`, and `file`, the action will complete successfully without any changes occurring. If `fail_no_op` is `true`, the action will fail. Note, however, that `fail_no_op` will only detect these specific no-op conditions; it is possible that no changes will occur if provided update(s) do not actually change any fields of matched record(s).

DELETE

The DELETE action deletes one or more records from a database.

*Note that deleted records and all associated data are **permanently deleted** and cannot be restored.*

This action requires the `DELETE` database privilege.

| Property | Value | Req | Default |
|------------|----------|-----|---------|
| action | "delete" | ? | |
| database | database | ? | |
| records | records | ? | |
| fail_no_op | boolean | | false |

TRASH

The TRASH action moves one or more records into the trash table of a database. This is only available in databases with the trash feature enabled, otherwise the action will fail.

This action requires the TRASH database privilege.

| Property | Value | Req | Default |
|------------|----------|-----|---------|
| action | "trash" | ? | |
| database | database | ? | |
| records | records | ? | |
| fail_no_op | boolean | | false |

RESTORE

The RESTORE action moves one or more records from the trash table of a database into the record table. This is only available in databases with the trash feature enabled, otherwise the action will fail.

If any records being restored have duplicate keys as other records currently in the database the action will fail.

This action requires the TRASH database privilege.

| Property | Value | Req | Default |
|------------|-----------|-----|---------|
| action | "restore" | ? | |
| database | database | ? | |
| records | records | ? | |
| fail_no_op | boolean | | false |

DISPOSE

The DISPOSE action deletes one or more records from the trash table of a database. This is only available in databases with the trash feature enabled, otherwise the action will fail.

*Note that disposed records and all associated data are **permanently deleted** and cannot be restored.*

This action requires the `DELETE` database privilege.

| Property | Value | Req | Default |
|------------|------------------------|-----|--------------------|
| action | <code>"dispose"</code> | ? | |
| database | <code>database</code> | ? | |
| records | <code>records</code> | ? | |
| fail_no_op | boolean | | <code>false</code> |

Admin Actions

Administrative actions create, modify, or delete XINA data structures, perform user management, or other system functions.

Schema Actions

SCHEMA

Returns the complete environment schema as a JSON object.

| Property | Value | Required | Default |
|----------|----------|----------|---------|
| action | "schema" | yes | |

Example

```
{
  "action" : "schema"
}
```

The server will return a JSON object:

```
{
  "groups" : [ ... ]
}
```

CREATE

The CREATE action is used to create new groups, databases, teams, and users.

CREATE GROUP

Creates a new group.

| Property | Value | Required | Default |
|----------|----------------------------------|----------|---------|
| action | "create" | yes | |
| create | "group" | yes | |
| group | group definition | yes | |

| Property | Value | Required | Default |
|----------|-------------------------------------|----------|---------|
| parent | group specifier | no | |
| teams | group teams association (see below) | no | |

If a `parent` group is provided, the created group will be a child of the parent; otherwise the group will be a root level group.

The `teams` property is used to associate the group with one or more teams on creation. This may either be a JSON array of team specifier(s), and the group will be added to those teams with the default group privileges as specified by each team, or may be a JSON object, with each key interpreted as a team specifier, and each value containing a JSON object of group privilege(s) to boolean values, overriding the default team privileges.

CREATE DATABASE

Creates a new database.

| Property | Value | Required | Default |
|----------|--|----------|---------|
| action | <code>"create"</code> | yes | |
| create | <code>"database"</code> | yes | |
| database | database definition | yes | |
| parent | group specifier | yes | |
| teams | database teams association (see below) | no | |

The `teams` property is used to associate the database with one or more teams on creation. This may either be a JSON array of team specifier(s), and the database will be added to those teams with the default database privileges as specified by each team, or may be a JSON object, with each key interpreted as a team specifier, and each value containing a JSON object of database privilege(s) to boolean values, overriding the default team privileges.

CREATE TEAM

Creates a new team.

| Property | Value | Required | Default |
|----------|---------------------------------|----------|---------|
| action | <code>"create"</code> | yes | |
| create | <code>"team"</code> | yes | |
| team | team definition | yes | |

CREATE USER

Creates a new user.

| Property | Value | Required | Default |
|----------|-----------------------|----------|---------|
| action | <code>"create"</code> | yes | |

| Property | Value | Required | Default |
|----------|---------------------------------|----------|---------|
| create | <code>"user"</code> | yes | |
| user | user definition | yes | |

ALTER

The ALTER action is used to edit group, database, field, team, or user properties.

ALTER GROUP SET

Alters one or more group parameters. Requires the `alter` privilege on the specified group.

| Property | Value | Required | Default |
|----------|---|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"group"</code> | yes | |
| op | <code>"set"</code> | yes | |
| group | group specifier | yes | |
| set | JSON object map of parameter(s) to value(s) | yes | |

ALTER GROUP OBJECTS

Inserts, updates, or deletes group objects. Requires the `alter` privilege on the specified group.

| Property | Value | Required | Default |
|----------|--|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"group"</code> | yes | |
| op | <code>"objects"</code> | yes | |
| group | group specifier | yes | |
| objects | JSON object map of key(s) to object value(s) | yes | |

Any properties in the `objects` JSON object with a `null` value will be deleted, if they exist in the group objects.

ALTER GROUP FILES

Inserts, updates, or deletes group files. Requires the `alter` privilege on the specified group.

| Property | Value | Required | Default |
|----------|----------------------|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"group"</code> | yes | |
| op | <code>"files"</code> | yes | |

| Property | Value | Required | Default |
|----------|---|----------|---------|
| group | group specifier | yes | |
| files | JSON object map of key(s) to object ID(s) | yes | |

Any properties in the `files` JSON object with a `null` value will be deleted, if they exist in the group files.

ALTER DATABASE SET

Alters one or more database parameters. Requires the `alter` privilege on the specified database.

| Property | Value | Required | Default |
|----------|---|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"database"</code> | yes | |
| op | <code>"set"</code> | yes | |
| database | database specifier | yes | |
| set | JSON object map of parameter(s) to value(s) | yes | |

ALTER DATABASE OBJECTS

Inserts, updates, or deletes database objects.

| Property | Value | Required | Default |
|----------|--|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"database"</code> | yes | |
| op | <code>"objects"</code> | yes | |
| database | database specifier | yes | |
| objects | JSON object map of key(s) to object value(s) | yes | |

Any properties in the `objects` JSON object with a `null` value will be deleted, if they exist in the database objects.

ALTER DATABASE FILES

Inserts, updates, or deletes database files. Requires the `alter` privilege on the specified database.

| Property | Value | Required | Default |
|----------|---|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"database"</code> | yes | |
| op | <code>"files"</code> | yes | |
| database | database specifier | yes | |
| files | JSON object map of key(s) to object ID(s) | yes | |

Any properties in the `files` JSON object with a `null` value will be deleted, if they exist in the database files.

ALTER DATABASE ADD FIELDS

Adds one or more fields to an existing database. Requires the `alter` privilege on the specified database.

This operation modifies the database table(s) and may take several hours for very large databases.

| Property | Value | Required | Default |
|----------|---------------------------------|----------|--------------------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"database"</code> | yes | |
| op | <code>"add_fields"</code> | yes | |
| database | database specifier | yes | |
| fields | JSON array of field definitions | yes | |
| first | <code>boolean</code> | no | <code>false</code> |
| after | field specifier | no | |

The action will fail if any of the new fields have the same name or label as eachother or any existing field in the database.

By default, new fields are added at the end of the existing fields. If `first` is true, new fields will be added at the front of the existing fields. If `after` is provided, new fields will be added immediately after the specified field, and before any following fields. If both `first` is `true` and `after` is provided, the action will fail.

ALTER DATABASE DROP FIELDS

Drops one or more fields from an existing database. Requires the `alter` privilege on the specified database.

This operation modifies the database table(s) and may take several hours for very large databases.

| Property | Value | Required | Default |
|----------|----------------------------|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"database"</code> | yes | |
| op | <code>"drop_fields"</code> | yes | |
| database | database specifier | yes | |
| fields | fields specifier | yes | |

The action will fail if any of the specified fields is a key field, or if the action would drop all fields from a database.

ALTER DATABASE ORDER FIELDS

Specifies ordering of one or more fields in a database. Requires the `alter` privilege on the specified database.

This operation does not modify the database table(s), only the field order as indicated by the XINA schema.

| Property | Value | Required | Default |
|----------|--------------------------------|----------|---------|
| action | "alter" | yes | |
| alter | "database" | yes | |
| op | "order_fields" | yes | |
| database | database specifier | yes | |
| fields | JSON array of field specifiers | yes | |
| after | field specifier | no | |

Fields will be ordered based on the order provided in the `fields` property, with any fields not specified maintaining their original order after the specified set. If `after` is provided, the ordered block will start following that specified field, with any non-specified fields before the `after` field maintaining their original order. If the `after` field is included in the `fields` property, the action will fail.

Example

Given a database `db` with the fields order `f1`, `f2`, `f3`, `f4`, `f5`, `f6`, the action:

```
{
  "action": "alter",
  "alter": "database",
  "database": "db",
  "op": "order_fields",
  "fields": ["f4", "f2"]
}
```

The resulting field order would be `f4`, `f2`, `f1`, `f3`, `f5`, `f6`.

Given the same intial setup and action but adding `"after": "f3"`, the resulting order would be: `f1`, `f3`, `f4`, `f2`, `f5`, `f6`

ALTER DATABASE RESET PARTITIONS

Resets one or more partitions of a database record table. Requires the `alter` privilege on the specified database.

*This action permanently deletes **all data in the specified partitions**.

Unlike the `DELETE` action, this action immediately frees storage space in the underlying database system.

| Property | Value | Required | Default |
|----------|--------------------|----------|---------|
| action | "alter" | yes | |
| alter | "database" | yes | |
| op | "reset_partitions" | yes | |
| database | database specifier | yes | |

| Property | Value | Required | Default |
|------------|--------------------------------------|----------|---------|
| partitions | partitions specifier | yes | |

ALTER FIELD SET

Alters one or more field parameters. Requires the `alter` privilege on the specified database.

| Property | Value | Required | Default |
|----------|---|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"field"</code> | yes | |
| op | <code>"set"</code> | yes | |
| database | database specifier | yes | |
| field | field specifier | yes | |
| set | JSON object map of parameter(s) to value(s) | yes | |

ALTER FIELD OBJECTS

Inserts, updates, or deletes field objects. Requires the `alter` privilege on the specified database.

| Property | Value | Required | Default |
|----------|--|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"field"</code> | yes | |
| op | <code>"objects"</code> | yes | |
| database | database specifier | yes | |
| field | field specifier | yes | |
| objects | JSON object map of key(s) to object value(s) | yes | |

Any properties in the `objects` JSON object with a `null` value will be deleted, if they exist in the field objects.

ALTER FIELD FILES

Inserts, updates, or deletes field files. Requires the `alter` privilege on the specified database.

| Property | Value | Required | Default |
|----------|------------------------------------|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"field"</code> | yes | |
| op | <code>"files"</code> | yes | |
| database | database specifier | yes | |
| field | field specifier | yes | |

| Property | Value | Required | Default |
|----------|---|----------|---------|
| files | JSON object map of key(s) to object ID(s) | yes | |

Any properties in the `files` JSON object with a `null` value will be deleted, if they exist in the field files.

ALTER USER SET

Alters one or more user parameters. Requires the `super` privilege to alter any user other than the current user.

| Property | Value | Required | Default |
|----------|---|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"user"</code> | yes | |
| op | <code>"set"</code> | yes | |
| user | user specifier | yes | |
| set | JSON object map of parameter(s) to value(s) | yes | |

ALTER USER OBJECTS

Inserts, updates, or deletes user objects. Requires the `super` privilege to alter any user other than the current user.

| Property | Value | Required | Default |
|----------|--|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"user"</code> | yes | |
| op | <code>"objects"</code> | yes | |
| user | user specifier | yes | |
| objects | JSON object map of key(s) to object value(s) | yes | |

Any properties in the `objects` JSON object with a `null` value will be deleted, if they exist in the user objects.

ALTER USER FILES

Inserts, updates, or deletes user files. Requires the `super` privilege to alter any user other than the current user.

| Property | Value | Required | Default |
|----------|---|----------|---------|
| action | <code>"alter"</code> | yes | |
| alter | <code>"user"</code> | yes | |
| op | <code>"files"</code> | yes | |
| user | user specifier | yes | |
| files | JSON object map of key(s) to object ID(s) | yes | |

Any properties in the `files` JSON object with a `null` value will be deleted, if they exist in the user files.

DROP

Permanently delete teams, groups, databases, or users.

DROP GROUP

Drops a group. This action requires the `super` privilege.

*This action permanently deletes **all data in the specified group**.*

| Property | Value | Required | Default |
|----------|----------------------|----------|--------------------|
| action | <code>"drop"</code> | yes | |
| drop | <code>"group"</code> | yes | |
| group | group specifier | yes | |
| children | <code>boolean</code> | no | <code>false</code> |

By default, if the specified group has any child groups or databases the action will fail. If `children` is `true`, all child groups and databases will also be dropped.

DROP DATABASE

Drops a database. This action requires the `super` privilege.

*This action permanently deletes **all data in the specified database**.*

| Property | Value | Required | Default |
|----------|-------------------------|----------|--------------------|
| action | <code>"drop"</code> | yes | |
| drop | <code>"database"</code> | yes | |
| database | database specifier | yes | |
| children | <code>boolean</code> | no | <code>false</code> |

By default, if the specified database has any child databases the action will fail. If `children` is `true`, all child databases will also be dropped.

DROP TEAM

Drops a team. This action requires the `super` privilege.

*This action permanently deletes **all data in the specified team**.*

| Property | Value | Required | Default |
|----------|---------------------|----------|---------|
| action | <code>"drop"</code> | yes | |

| Property | Value | Required | Default |
|----------|--------------------------------|----------|---------|
| drop | <code>"team"</code> | yes | |
| team | team specifier | yes | |

DROP USER

Drops a user. This action requires the `super` privilege.

*This action permanently deletes **all data associated with the specified user.***

| Property | Value | Required | Default |
|----------|--------------------------------|----------|---------|
| action | <code>"drop"</code> | yes | |
| drop | <code>"user"</code> | yes | |
| user | user specifier | yes | |

JOIN

The JOIN action joins groups, databases, or users to one or more teams.

JOIN GROUPS

JOIN DATABASES

JOIN USERS

LEAVE

The LEAVE action removes groups, databases, or users from one or more teams.

LEAVE GROUPS

LEAVE DATABASES

LEAVE USERS

User Actions

GRANT

REVOKE

REQUEST

Request an arbitrary action to be performed by a user with required permissions.

RETRACT

Retract one or more user requests.

APPROVE

REJECT

System Functions

ACCESS

Used to acquire temporary access ID for websocket connection.

Example

```
{  
  "action" : "access"  
}
```

Result

```
{  
  "access_id" : "<string>"  
  "expires" : <unix_ms_timestamp>
```


Task and Thread Actions

Task actions provide features for running and interacting with asynchronous tasks managed by the XINA Run application or AWS Lambda platform.

Task Reference

Task Actions may reference existing tasks by either their numeric Task ID or a JSON object with the following format:

```
{
  "ref": [<ref_id assigned when creating the task>],
  "type": "ref"
}
```

The `ref_id` is an arbitrary, optional value defined in the Task Definition when a task is created. The `ref_id` does not have to be unique, implying the Task Action will be performed on all tasks that match the `ref_id`.

Task Actions

RUN

Run one or more asynchronous tasks.

Example

```
{
  "action" : "run",
  "tasks" : [ <task definition or reference>, ... ]
}
```

Task Definition

A task definition is used to define a new Task. It has a JSON object with the following format:

```
{
  "name"    : <string, task name>,
  "conf"    : <JSON object, format depends on task>,
  "parent"  : <long, parent task ID, optional>,
```

```
"thread" : <string, thread name, optional>,  
"auto" : <boolean, optional, default false>,  
"archive" : <boolean, optional, default false - if true, task workspace will not be deleted>,  
"open" : <boolean, optional, default false>,  
"desc" : <string, optional>,  
"priority" : <int, optional>,  
"timeout" : <int, ms, optional>,  
"ref_id" : <long, optional - arbitrary value for Task Referencing>  
}
```

CONCLUDE

Explicitly conclude an asynchronous task. This is currently only used by AWS Lambda tasks, to notify the XINA server that the task has concluded. If a value is provided for `"delay"`, the server will wait that many milliseconds before concluding the task. This supports tasks that may have a longer cleanup or import period following the immediate task completion.

Example

```
{  
  "action" : "conclude",  
  "task" : <task ID>,  
  "delay" : <number, ms, 0-5000, optional, default 0>  
}
```

CANCEL

Cancel one or more asynchronous tasks.

Only non-concluded tasks may be canceled. If "ignore" is false, and any specified tasks have concluded, an error will be thrown and no changes will occur. If "ignore" is true, all non-concluded specified tasks will be canceled, and any concluded tasks will be ignored.

Example

```
{  
  "action" : "cancel",  
  "tasks" : [ <task reference>, ... ],  
  "ignore" : <boolean, optional, default false>  
}
```

CLEAN

Permanently delete one or more asynchronous task records and any associated files.

Only concluded tasks may be cleaned. If `"ignore"` is `false`, and any specified tasks have not concluded, an error will be thrown and no changes will occur. If `"ignore"` is `true`, all concluded specified tasks will be cleaned, and any non-concluded tasks will be ignored.

Example

```
{
  "action" : "clean",
  "tasks" : [ <task reference>, ... ],
  "ignore" : <boolean, optional, default false>
}
```

DESTROY

Cancel and clean one or more asynchronous tasks. Unlike the CANCEL and CLEAN actions, this will apply to all tasks regardless of the current task state.

Example

```
{
  "action" : "clean",
  "tasks" : [ <task reference>, ... ]
}
```

Thread Actions

PAUSE

Pause execution of one or more asynchronous task threads. This does not affect any task currently running in the thread, but future tasks assigned to the thread will not run until the thread is resumed.

Example

```
{
  "action" : "pause",
  "threads" : [ <string, thread name>, ... ]
}
```

```
}
```

RESUME

Resume execution of one or more asynchronous task threads. If `"continue"` is `true` and a continuable task is currently locked on the thread, that task will be continued.

Example

```
{  
  "action" : "pause",  
  "threads" : [ <string, thread name>, ... ],  
  "continue" : <boolean, optional, default false>  
}
```

Struct Actions

Struct actions are complex data actions designed to be used with [XINA Structs](#). Unlike most API actions, they may involve complex multi-step operations, and are dependent on the structs configuration of groups and databases.

Data Actions

STRUCT BUFFER IMPORT

Imports a [buffer data file](#) into a pipe.

| Property | Value | Req | Default |
|----------|--------------------------------------|-----|---------|
| action | "struct_buffer_import" | ? | |
| pipe | pipe group specifier | ? | |
| file | binary object | ? | |
| format | string | ? | |
| conf | jsonobject | | |

When a data set is imported the XINA server will run the following steps:

- For each row:
 - validate time and value
 - process mnemonic
 - If mnemonic ID
 - If found in definitions database:
 - If mnemonic is deprecated, throw error
 - Else, use mnemonic for row
 - Else, throw error due to unrecognized ID
 - Else, parse name and optional unit
 - If name match found:
 - If unit is provided and does not match, throw error
 - If mnemonic is deprecated, throw error
 - Else, use mnemonic for row
 - Else, mnemonic is new, create new temporary mnemonic definition based on provided information
- If any rows contain same mnemonic and time, throw error
- Check for time overlap in database
 - If found
 - If `on_overlap = fail`, throw error
 - Else If `on_overlap = delete`, delete all data from database in time range of imported data
 - Else (`on_overlap = ignore`), do nothing
- If new mnemonic definitions created, insert into mnemonic definition database
- Insert data into mnemonic database

STRUCT MN ALIAS

Adds one or more aliases of name/unit pairs to a single existing mnemonic.

| Property | Value |
|-----------------------|---|
| <code>action</code> | <code>"struct_mn_edit"</code> |
| <code>database</code> | mnemonic definition database specifier |
| <code>mn</code> | mnemonic ID |
| <code>aliases</code> | <code>string[]</code> , name/unit pair alias(es) for mnemonic |

STRUCT MN EDIT

Edits one or more properties of a single existing mnemonic.

| Property | Value | Required |
|-----------------------|---|----------|
| <code>action</code> | <code>"struct_mn_edit"</code> | ? |
| <code>database</code> | mnemonic definition database specifier | ? |
| <code>mn</code> | mnemonic ID | ? |
| <code>name</code> | <code>string</code> , new name/unit pair for mnemonic | |
| <code>state</code> | <code>string</code> | |

STRUCT MN MERGE

Merges one or more existing mnemonics into a single existing mnemonic.

STRUCT EVENT

Performs context-aware event operations.

Unlike typical record operations, these actions support event definition lookup and creation. Event records or updates may specify a `"name"` property, as if it were a database field. This will be used to lookup a corresponding event ID from the event definitions associated with the database, and create a new definition with the name if one is not found. Alternatively, the `"name"` may reference an event definition by external ID, by starting with the `$` character.

If an event specifies both a `"name"` and `"e_id"`, the action will fail, as the outcome is ambiguous. If the `"name"` property value is numeric or numeric text, it will interpreted as a direct event ID reference (as if it had been provided as `"e_id"`).

"e_id" values are validated against existing event definitions, and the action will fail if the event ID is not found.

STRUCT EVENT INSERT

Inserts one or more events into a single event database.

| Property | Value | Req | Default |
|----------|----------------|-----|---------|
| action | "struct_event" | ? | |
| op | "insert" | ? | |
| database | event database | ? | |
| events | event records | ? | |

If the event database has an associated event change database, the event change database will be checked for any update records, and the changes will be applied to the incoming events before they are inserted.

If any inserted UEIDs are already present in the database, the action will fail.

STRUCT EVENT CLOSE

Closes one or more open interval event(s).

| Property | Value | Req | Default |
|----------|--------------------------|-----|---------|
| action | "struct_event" | ? | |
| op | "close" | ? | |
| database | event database | ? | |
| t | instant(us) closing time | | now |
| events | events specifier | ? | |
| fields | field value map | | |

The closing time is specified by the t property.

The events property is an extension of the standard records specifier, but may include UEID(s) as strings. Only currently open intervals in the specified database will be affected.

If the fields property is provided, updates the value(s) of the specified field(s) in the map for all events being closed.

STRUCT EVENT UPDATE

Updates one or more events.

| Property | Value | Req | Default |
|----------|-------------------------|-----|---------|
| action | "struct_event" | ? | |
| op | "update" | ? | |
| database | event database | ? | |
| t | instant(us) update time | | now |

| Property | Value | Req | Default |
|----------|--------------------|-----|---------|
| events | events specifier | | |
| fields | field(s) to update | ? | |

If the event database is a child of a pipe, an event change record is inserted in the associated event change database for each event UEID matching the specifier. Additionally, if any updated fields are not configured to permit updating, the action will fail.

STRUCT EVENT CLEAR

Schema Actions

STRUCT CREATE

The STRUCT CREATE action is used to create a variety of XINA Structs compatible schema elements.

STRUCT CREATE PROJECT

Creates a structs project group.

| Property | Value | Req | Default |
|----------------|---------------------------------|-----|---------|
| action | <code>"struct_create"</code> | ? | |
| create | <code>"project"</code> | ? | |
| parent | group specifier | | |
| name | <code>string</code> | ? | |
| label | <code>string</code> | | name |
| desc | <code>string</code> | | label |
| group_teams | team group privilege map | | |
| database_teams | team database privilege map | | |

If a `parent` group is specified, it may not include a structs definition (since project groups must be at the top level of a struct heirarchy). The `name` (and `label`, if provided) must not be in use by any group siblings, or the action will fail.

STRUCT CREATE CATEGORY

Creates a structs category group.

| Property | Value | Req | Default |
|----------|------------------------------|-----|---------|
| action | <code>"struct_create"</code> | ? | |
| create | <code>"category"</code> | ? | |

| Property | Value | Req | Default |
|----------------|-----------------------------|-----|---------|
| parent | group specifier | ? | |
| name | string | ? | |
| label | string | | name |
| desc | string | | label |
| group_teams | team group privilege map | | |
| database_teams | team database privilege map | | |

The `parent` group must be either a project group or category group, or the action will fail. The `name` (and `label`, if provided) must not be in use by any group siblings, or the action will fail.

STRUCT CREATE MODEL

Creates a structs model group.

| Property | Value | Req | Default |
|----------------|-----------------------------|-----|---------|
| action | "struct_create" | ? | |
| create | "model" | ? | |
| parent | group specifier | ? | |
| name | string | ? | |
| label | string | | name |
| desc | string | | label |
| event | boolean | | false |
| eventf | boolean | | false |
| eventfs | boolean | | false |
| group_teams | team group privilege map | | |
| database_teams | team database privilege map | | |

The `parent` group must be either a project group or category group, or the action will fail. The `name` (and `label`, if provided) must not be in use by any group siblings, or the action will fail.

STRUCT CREATE PIPE

Creates a struct pipe group.

| Property | Value | Required | Default |
|----------|-----------------|----------|---------|
| action | "struct_create" | ? | |
| create | "pipe" | ? | |
| model | group specifier | ? | |
| name | string | ? | |
| label | string | | name |

| Property | Value | Required | Default |
|----------------|--|----------|---------|
| desc | string | | label |
| group_teams | team group privilege map | | |
| database_teams | team database privilege map | | |
| partition | boolean or {"from": <start year>, "to": <end year>} | | false |
| | See the pipe definition for other supported properties | | |

The `parent` group must be either a project group or category group, or the action will fail. The `name` (and `label`, if provided) must not be in use by any group siblings, or the action will fail.

STRUCT CREATE DEF

Creates a structs definitions group, with associated databases.

| Property | Value | Req | Default |
|----------|---------------------------------|-----|---------|
| action | "struct_create" | ? | |
| create | "def" | ? | |
| parent | group specifier | ? | |

The `parent` group must be either a project, category, or model group, or the action will fail.

STRUCT CREATE EVENT

Creates a new structs event database.

| Property | Value | Req | Default |
|----------|--|-----|---------------------------------|
| action | "struct_create" | ? | |
| create | "event" | ? | |
| group | group specifier | ? | |
| type | "none", "file", or "files" | | "none" |
| name | string | | "event", "eventf", or "eventfs" |
| label | string | | name |
| desc | string | | label |
| singular | string | | "event" |
| plural | string | | singulars |
| conf | JSON object | | |
| fields | array of field definitions | | |
| teams | team database privilege map | | |

STRUCT CREATE NOTEBOOK

Creates a new structs notebook database.

| Property | Value | Req | Default |
|----------|--|-----|---------|
| action | <code>"struct_create"</code> | ? | |
| create | <code>"notebook"</code> | ? | |
| parent | group specifier | ? | |
| name | string | ? | |
| label | string | | name |
| desc | string | | label |
| fields | array of field definitions | | |
| teams | team database privilege map | | |

Specifier Syntax

Specifiers are objects which specify schema or data elements.

In general a specifier is an object with a `type` property indicating the type of the specifier. Some specifiers provide a shorthand version by substituting a different JSON data type.

Common

There are several common specifiers used by multiple components.

All

Specifies all elements in the current context (for example, as a records specifier all would include all records in the selected database).

| Property | Value |
|-------------------|--------------------|
| <code>type</code> | <code>"all"</code> |

Example

```
{ "type": "all" }
```

ID

Specifies an element by numeric ID. The value is provided directly as a JSON number.

Example (JSON number)

```
123
```

Name

Specifies an element by name. The value is provided directly as a JSON string.

Example (JSON string)

```
"foo"
```

Where

Specifies element(s) meeting a condition provided by an [expression](#).

The source against which the expression is used depends on the context, but in general can be represented as

```
SELECT [elements] FROM [source] WHERE [expression]
```

where source is the table containing the element.

| Property | Value |
|----------|----------------------------|
| type | "where" |
| where | expression |

Array

Specifies elements using an array of singular specifiers. The value is provided directly as a JSON array.

The types of the individual specifiers depend on the element, but in general unless otherwise noted all singular specifier types for the element may be used. Specifier types may also be intermingled.

Example (JSON array)

```
[ 123, "foo", {"type": "where", "where", "..."} ]
```

Schema Elements

Groups

Specifies one or more groups. [Group specifiers](#) are also valid groups specifiers.

- [All](#)
- [Array](#)

Group

Specifies a single group.

- [ID](#)
- [Name](#)

Databases

Specifies one or more databases. [Database specifiers](#) are also valid databases specifiers.

- [All](#)
- [Array](#)

Database

Specifies a single database.

- [ID](#)
- [Name](#)

Fields

Specifies one or more fields. [Field specifiers](#) are also valid fields specifiers.

- [All](#)
- [Array](#)

Field

Specifies a single field.

- [ID](#)
 - [Name](#)
-

Walls

Specifies one or more walls. [Wall specifiers](#) are also valid walls specifiers.

- [Array](#)
-

Wall

Specifies a single wall.

Group Wall

Specifies the wall of single group.

| Property | Value |
|----------|-----------------|
| type | "group" |
| group | group specifier |

Example

```
{
  "type" : "group",
  "group" : "foo"
}
```

Database Wall

Specifies the wall of single database.

| Property | Value |
|----------|--------------------|
| type | "database" |
| database | database specifier |

Example

```
{
  "type" : "database",
  "database" : "foo"
}
```

Record Wall

Specifies the wall of single record.

| Property | Value |
|----------|--------------------|
| type | "record" |
| database | database specifier |
| record | record specifier |

Example

```
{
  "type" : "database",
  "database" : "foo",
  "record" : 123
}
```

```
}
```

User Wall

Specifies the wall of single user.

| Property | Value |
|-------------------|--------------------------------|
| <code>type</code> | <code>"user"</code> |
| <code>user</code> | user specifier |

Example

```
{  
  "type" : "user",  
  "user" : "foo"  
}
```

Data Elements

Records

Specifies a set of records in a single database. [Record specifiers](#) are also valid records specifiers.

- [All](#)
- [Array](#)
- [Where](#)

Record

Specifies a single record in a database.

- `ID`

Key

Specifies a single record by a set of key value(s).

```
{ "type" : "key", "key" : <[[XINA API :: Data Syntax#Fields|fields]]> }
```

Each key must specify a non-null value for each key field of the database.

Posts

Specifies a set of posts. [Post specifiers](#) are also valid posts specifiers.

- [All](#)
 - [Array](#)
 - [Where](#)
-

Post

Specifies a single post.

- [ID](#)

Administrative

Users

Specifies a set of users. [User specifiers](#) are also valid users specifiers.

- [All](#)
 - [Array](#)
 - [Where](#)
-

User

Specifies a single user. Note that [name](#) in this case refers to the username, not the user's full name.

- [ID](#)
 - [Name](#)
-

Group Privileges

Specifies a set of group privileges.

- [All](#)
 - [Array](#)
-

Group Privilege

Specifies a single group privilege as a JSON string. The valid group privileges are:

- "select"
 - "post"
 - "reply"
 - "alter"
 - "grant"
-

Database Privileges

Specifies a set of database privileges.

- All
 - Array
-

Database Privilege

Specifies a single database privilege as a JSON string. The valid database privileges are:

- "select"
- "post"
- "reply"
- "update"
- "insert"
- "trash"
- "delete"
- "lock"
- "alter"
- "grant"

Record Syntax

JSON Format

A single record may be encoded as a JSON object:

| Property | Value |
|----------------------------|---|
| <field name / label> | field type appropriate value / <code>null</code> |
| <code>"expressions"</code> | JSON object mapping field name/label to expression |
| <code>"file"</code> | binary object (if database has <code>file</code> enabled) |
| <code>"tags"</code> | JSON array of string(s) (if database has <code>tag</code> enabled) |

The `"expressions"` property allows field values to be specified by expression, rather than explicit value. Between the base object and `"expressions"` object, field may only have a single value provided, or an error will be thrown.

Multiple records may be encoded as a JSON array of JSON objects in this format.

DSV Format

Record data may be provided in a delimiter separated values format. In this case the record data itself is contained in a [binary object](#).

| Property | Value |
|--------------------------|---|
| <code>"type"</code> | <code>"dsv"</code> , <code>"csv"</code> , or <code>"tsv"</code> |
| <code>"file"</code> | binary object |
| <code>"delimiter"</code> | string (required for <code>"dsv"</code>) |
| <code>"quote"</code> | string (optional) |

The `"csv"` and `"tsv"` types specify default delimiters of comma (,) and tab (\t), respectively.

Example

```
{
  "records": {
    "type": "dsv",
    "file" : "<object ID>",
    "delimit": ";",
  }
}
```

The format of the separated values file is largely based on the [RFC 4180 standard](#). The specific requirements are:

- lines must end with `LF` (`\n`) or `CR LF` (`\r\n`)
- line breaks cannot be used in values
- the default quote character is `"` (double quotes)
- any field *may* be quoted by the quote character
- any field containing the delimiter must be quoted
- a quote character in a quoted value must be represented by two quote characters
- the first row must contain the names of each field
- blank lines with no data are ignored

Expression Syntax

XINA expressions translate to MySQL expressions, which are evaluated as a query is executed.

All expressions have a **standard form** as a JSON object, with a `type` property specifying the expression type, and additional properties as needed by that expression type.

Additionally, certain expression types may be represented using a **short form**, which is formatted as a JSON object with a single property prefixed with the `$` character.

Literals

Literal expressions represent a single, discrete value.

Null

The MySQL `NULL` value. May also be specified with the JSON `null` value.

| Property | Value |
|-------------------|---------------------|
| <code>type</code> | <code>"null"</code> |

Example (as object)

```
{ "type": "null" }
```

Example (as JSON literal)

```
null
```

Number

A numeric literal value. The value may be provided as a native JSON number, or encoded as a string. May also be provided directly as a JSON `number` value.

| Property | Value |
|--------------------|--|
| <code>type</code> | <code>"number"</code> |
| <code>value</code> | <code>number</code> or <code>string</code> |

Example (as object)

```
{
  "type" : "number",
  "value" : 123
}
```

Example (as JSON literal)

```
123
```

String

A string literal value. May also be provided directly as a JSON `string`.

| Property | Value |
|--------------------|-----------------------|
| <code>type</code> | <code>"string"</code> |
| <code>value</code> | <code>string</code> |

Example (as object)

```
{
  "type" : "string",
  "value" : "foo"
}
```

Example (as JSON literal)

```
"foo"
```

Datetime

A datetime literal value. Interpreted by the database as Unix time in milliseconds.

| Property | Value |
|--------------------|--|
| <code>type</code> | <code>"datetime"</code> or <code>"dt"</code> |
| <code>value</code> | <code>integer</code> or <code>string</code> |

If the value provided is an `integer` it must be the number of milliseconds since the Unix epoch. If the value is a `string` it must be encoded according to the following syntax, taken from the ISO8601 standard:


```
date-opt-time    = date-element ['T' [time-element] [offset]]
date-element     = std-date-element | ord-date-element | week-date-element
std-date-element = yyyy ['- MM ['- dd]]
ord-date-element = yyyy ['- DDD]
week-date-element = xxxx '-W' ww ['- e]
time-element     = HH [minute-element] | [fraction]
minute-element   = ':' mm [second-element] | [fraction]
second-element   = ':' ss [fraction]
fraction         = ('.' | ',') digit [digit] [digit]
offset           = 'Z' | (('+' | '-') HH ['- mm ['- ss [('-' | ',') SSS]]])
```

If the offset is not provided the timezone will be assumed to be UTC.

Supports shorthand syntax with the `$dt` property.

| Property | Value |
|-------------------|---|
| <code>\$dt</code> | <code>integer</code> or <code>string</code> |

Local Datetime

A local datetime literal value.

| Property | Value |
|--------------------|--|
| <code>type</code> | <code>"localdatetime"</code> or <code>"ldt"</code> |
| <code>value</code> | <code>string</code> |

The value must be encoded according to the same syntax as the datetime literal, except with the offset omitted.

Supports shorthand syntax with the `$ldt` property.

| Property | Value |
|--------------------|---------------------|
| <code>\$ldt</code> | <code>string</code> |

Local Date

A local date literal value.

| Property | Value |
|--------------------|---|
| <code>type</code> | <code>"localdate"</code> or <code>"ld"</code> |
| <code>value</code> | <code>string</code> |

The value must be encoded according to the same syntax as the `date-element` in the datetime literal.

Supports shorthand syntax with the `$ld` property.

| Property | Value |
|-------------------|---------------------|
| <code>\$ld</code> | <code>string</code> |

Local Time

A local time literal value.

| Property | Value |
|--------------------|---|
| <code>type</code> | <code>"localtime"</code> or <code>"lt"</code> |
| <code>value</code> | <code>string</code> |

The value must be encoded according to the same syntax as the `time-element` in the datetime literal.

Supports shorthand syntax with the `$lt` property.

| Property | Value |
|-------------------|---------------------|
| <code>\$lt</code> | <code>string</code> |

Columns

Column expressions specify a column of a table. Although each column type has a separate full syntax, there is a shorthand syntax with the `$col` property, which infers the column type based on the content.

| Property | Value |
|--------------------|----------------------------|
| <code>\$col</code> | <code>string</code> column |

```
column      = system-column | database-column
system-column = system-table-name '.' system-parameter-name
database-column = database-path ['@' database-table-name] '.' (parameter-name | attribute-name | field-name | blob-attribute)
blob-attribute = blob-name ':' blob-attribute-name
```

Examples

- `user.email` : `email` parameter of the `user` system table
- `a.b.record_id` : `record_id` attribute of the `record` table of database `b` in group `a`
- `a.b@trash.record_id` : `record_id` attribute of the `trash` table of database `b` in group `a`
- `a.b.c` : `c` field of the `record` table of database `b` in group `a`

System Parameter Column

Specifies a column of a system table.

| Property | Value |
|----------|----------|
| type | "column" |
| table | string |
| column | string |

Database Parameter Column

Specifies a parameter column of a database table.

| Property | Value |
|----------|-----------------------|
| type | "column" |
| database | database specifier |
| table | string table name |
| column | string parameter name |

Database Attribute Column

Specifies an attribute column of a database table.

| Property | Value |
|----------|-----------------------|
| type | "column" |
| database | database specifier |
| table | string table name |
| column | string attribute name |

Database Field Column

Specifies a field column of a database table.

| Property | Value |
|----------|--------------------|
| type | "column" |
| database | database specifier |
| table | string table name |
| column | field specifier |

Alias

Although the alias is not technically a column, it can refer directly by name to any column in the source, or to an alias of a result column.

| Property | Value |
|----------|---------|
| type | "alias" |
| value | string |

Supports shorthand syntax with the `$alias` property.

| Property | Value |
|----------|--------|
| \$alias | string |

Evaluations

Evaluations are expressions evaluated by MySQL.

Between

Returns true if the expression `e` is between `min` and `max`.

| Property | Value |
|----------|------------|
| type | "between" |
| e | expression |
| min | expression |
| max | expression |

Supports shorthand syntax with the `$between` property. Takes a JSON array of exactly 3 expressions, in the order `e`, `min`, and `max`.

| Property | Value |
|-----------|----------------------------|
| \$between | array of three expressions |

Binary

Binary operation, evaluated as `e1` `op` `e2`.

| Property | Value |
|----------|------------|
| type | "binary" |
| op | string |
| e1 | expression |
| e2 | expression |

Valid binary operators are as follows:

| Operator | Description |
|----------|---|
| and | logical AND |
| or | logical OR |
| = | equal |
| != | not equal |
| > | greater |
| >= | greater or equal |
| < | less |
| <= | less or equal |
| is | test against <code>NULL</code> |
| like | simple pattern matching, see here |
| regexp | advanced pattern matching, see here |
| + | addition |
| - | subtraction |
| * | multiplication |
| / | division |
| % | modulus |
| & | bit-wise AND |
| | bit-wise OR |
| << | left shift |
| >> | right shift |

Supports shorthand syntax with any operator by prefixing it with `$`. Takes a JSON array of two or more expressions. If more than two expressions are provided, behavior depends on the operator type. Logic and math operators perform each binary operation in order of expressions. For example:

- `{"$and": [true, true, false]}` = `(true and true) and false` = `false`
- `{"$/": [12, 3, 2, 2]}` = `((12 / 3) / 2) / 2` = `1`

Comparison operators perform a logical AND of the comparisons of the first expression to each additional expression.

- `{"$=": [0, 1, 2]} = (0 = 1) and (0 = 2) = false`

Case

Case logic expression. If the `base` is provided, returns the `then` expression of the first case in which `when` = `base`. Otherwise returns the first case in which `when` is `true`. If no case is satisfied returns `else` if it is provided, or `NULL` otherwise.

| Property | Value |
|--------------------|---|
| <code>type</code> | <code>"case"</code> |
| <code>base</code> | <code>expression</code> (optional) |
| <code>cases</code> | <code>array</code> of <code>case options</code> |
| <code>else</code> | <code>expression</code> (optional) |

Case Option

| Property | Value |
|-------------------|-------------------------|
| <code>when</code> | <code>expression</code> |
| <code>then</code> | <code>expression</code> |

Collate

Performs the MySQL `COLLATE` function.

| Property | Value |
|------------------------|-------------------------|
| <code>type</code> | <code>"collate"</code> |
| <code>e</code> | <code>expression</code> |
| <code>collation</code> | <code>string</code> |

Count Rows

Performs the MySQL `COUNT(*)` function.

| Property | Value |
|-------------------|---------------------------|
| <code>type</code> | <code>"count_rows"</code> |

Example

```
{ "type": "count_rows" }
```

Exists

Returns true if the enclosed `SELECT` returns at least one row.

| Property | Value |
|---------------------|-----------------------|
| <code>type</code> | <code>"exists"</code> |
| <code>select</code> | <code>select</code> |

Supports shorthand syntax with the `$exists` property.

| Property | Value |
|-----------------------|---------------------|
| <code>\$exists</code> | <code>select</code> |

Function

Performs a MySQL function. The number of arguments varies depending on the function.

| Property | Value |
|-----------------------|-----------------------------------|
| <code>type</code> | <code>"function"</code> |
| <code>function</code> | <code>string</code> |
| <code>args</code> | array of <code>expressions</code> |

Available functions are:

| Name | Args | Aggregate | Description |
|-----------------------------|----------------|-----------|---|
| <code>AVG</code> | 1 | yes | arithmetic average |
| <code>AVG_DISTINCT</code> | 1 | yes | arithmetic average of distinct values of argument |
| <code>BIT_AND</code> | 1 | yes | bit-wise AND |
| <code>BIT_OR</code> | 1 | yes | bit-wise OR |
| <code>BIT_XOR</code> | 1 | yes | bit-wise XOR |
| <code>CEIL</code> | 1 | yes | returns the smallest integer value not less than the argument |
| <code>COUNT</code> | 1 | yes | returns the number of rows in the which the argument is not <code>NULL</code> |
| <code>COUNT_DISTINCT</code> | <code>n</code> | yes | returns the number of distinct value(s) of the arguments |

| Name | Args | Aggregate | Description |
|--------------|------|-----------|---|
| FLOOR | 1 | yes | returns the largest integer value not greater than the argument |
| MAX | 1 | yes | returns the maximum value of the argument |
| MIN | 1 | yes | returns the minimum value of the argument |
| POW | 2 | no | |
| STDDEV_POP | 1 | yes | returns the population standard deviation of the argument |
| STDDEV_SAMP | 1 | yes | returns the sample standard deviation of the argument |
| SUM | 1 | yes | returns the sum of the argument |
| SUM_DISTINCT | 1 | yes | returns the sum of the distinct values of the argument |
| TRUNCATE | 2 | no | |
| VAR_POP | 1 | yes | returns the population variance of the argument |
| VAR_SAMP | 1 | yes | returns the sample variance of the argument |

Supports shorthand syntax by prefixing any function name with `$$`. For example, `{ "$$pow": [2, 3] }` evaluates to `8`.

In

Returns true if an expression is contained in a set of values. If an empty array is provided for `values`, will always return false.

| Property | Value |
|----------|--------------------------------------|
| type | "in" |
| e | expression |
| values | array of expressions |

Supports shorthand syntax with the `$in` property. Takes an array of a single expression (`e`), followed by either an array of expression(s) (`values`) or a `SELECT` object.

| Property | Value |
|----------|---|
| \$in | array of one expression , then either an array of expressions or a select |

In Select

Returns true if `e` is in the result of the `select` query.

| Property | Value |
|---------------------|----------------------------|
| <code>type</code> | <code>"in_select"</code> |
| <code>e</code> | expression |
| <code>select</code> | select |

Supports shorthand syntax with the `$in` property (see [above](#)).

Select Expression

Returns the value of the first column in the first row of the result set of the query.

| Property | Value |
|---------------------|------------------------|
| <code>type</code> | <code>"select"</code> |
| <code>select</code> | select |

Supports shorthand syntax with the `$select` property.

| Property | Value |
|-----------------------|------------------------|
| <code>\$select</code> | select |

Unary Expression

Unary operator expression, evaluated as `op e`.

| Property | Value |
|-------------------|----------------------------|
| <code>type</code> | <code>"unary"</code> |
| <code>op</code> | <code>string</code> |
| <code>e</code> | expression |

Valid unary operators are:

| Operator | Description |
|------------------|-------------|
| <code>not</code> | logical NOT |
| <code>-</code> | negate |
| <code>~</code> | bit invert |

Supports shorthand syntax with any operator by prefixing it with `$`. Takes a single expression as a value.

| Property | Value |
|----------|-------|
|----------|-------|

| | |
|-------|------------|
| \$ op | expression |
|-------|------------|

Select Syntax

The SELECT syntax is essentially a JSON representation of the MySQL `SELECT` syntax. See the [MySQL documentation](#) for more detailed information.

SELECT

The SELECT syntax is contained in a single JSON object.

| Property | Value | Notes |
|----------|---|--|
| distinct | <code>boolean</code> , default <code>false</code> | If <code>true</code> , only returns unique values |
| columns | result columns | If empty, returns all columns available from source |
| from | source | Source being selected from |
| where | expression | Condition for rows, where expression returns <code>true</code> |
| group | <code>array</code> of expressions | Used to group rows for aggregation functions |
| having | expression | Like <code>where</code> , but can filter aggregation results |
| order | <code>array</code> of order terms | Used to sort the results |
| limit | expression | Limit the number of rows returned |
| offset | expression | Offset of the start of the rows |

Result Columns

Specifies the column(s) to select.

All

Specifies all columns from the source. This is the same as the MySQL `SELECT *` syntax. This is the default if no value for the `columns` property is set.

| Property | Value |
|-------------------|--------------------|
| <code>type</code> | <code>"all"</code> |

Example

```
{ "type": "all" }
```

Array

Specifies column(s) as an array of [result column](#) objects. This is provided directly as a JSON array.

Example as JSON array:

```
[ ... ]
```

Result Column

Specifies an expression and optional alias. The alias can be referenced in the where clause with an alias expression.

| Property | Value |
|--------------------|--------------------------------|
| <code>e</code> | expression |
| <code>alias</code> | <code>string</code> (optional) |

Source

A source is a SQL table (or virtual table) from which a `SELECT` statement loads data.

Table Source

A source from any table.

| Property | Value |
|--------------------|--------------------------------|
| <code>type</code> | <code>"table"</code> |
| <code>table</code> | <code>string</code> table |
| <code>alias</code> | <code>string</code> (optional) |

The table syntax is the same as the table portion of the [column expression syntax](#)

```
table      = system-table-name | database-table
database-table = database-path ['@' database-table-name]
```

May also be provided directly as a JSON string (without the `alias` property).

System Table Source

Deprecated

A source from a system table.

| Property | Value |
|----------|------------------------|
| type | "table_system" or "ts" |
| table | string table name |
| alias | string (optional) |

Database Table Source

A source from a database table.

| Property | Value |
|----------|--------------------------|
| type | "table_database" or "td" |
| database | database specifier |
| table | string table name |
| alias | string (optional) |

Join Source

A source derived from a SQL join of two sources.

| Property | Value |
|----------|---|
| type | "join" |
| op | "join", "left", "left_outer", "inner", or "cross" |
| s1 | left join source |
| s2 | right join source |

Select Source

Source from the result of a select statement.

| Property | Value |
|----------|----------|
| type | "select" |
| select | select |

Order Term

Specifies an expression and optional order.

| Property | Value |
|----------|---|
| e | expression |
| order | "asc" or "desc" (optional, default "asc") |

Definitions Syntax

Under Construction

Group

Defines a XINA group.

| Property | Value |
|----------|--------|
| name | string |
| desc | string |

Database

Defines a XINA database. The `name` and `fields` values are required, and at least one field must be provided. If `label` is not provided it will be the same as `name`.

| Property | Value |
|-----------|---|
| name | string |
| label | string (optional) |
| format | string (optional) |
| path | string (optional) |
| desc | string (optional) |
| dynamic | boolean (optional, default <code>false</code>) |
| event | boolean (optional, default <code>false</code>) |
| file | boolean (optional, default <code>false</code>) |
| link | boolean (optional, default <code>false</code>) |
| lock | boolean (optional, default <code>false</code>) |
| log | boolean (optional, default <code>false</code>) |
| notify | boolean (optional, default <code>false</code>) |
| subscribe | boolean (optional, default <code>false</code>) |
| tag | boolean (optional, default <code>false</code>) |
| track | boolean (optional, default <code>false</code>) |

| Property | Value |
|-----------|------------------------------------|
| trash | boolean (optional, default false) |
| wall | boolean (optional, default false) |
| objects | object (optional) |
| files | object (optional) |
| fields | array of fields |
| blobs | array of blobs (optional) |
| indexes | array of string values (optional) |
| databases | array of databases (optional) |

Field

Defines a XINA database field. The `name` and `type` are required. If `label` is not provided it will be the same as `name` .

```
{
  "name" : <string>,
  "label" : <string>, (optional)
  "type" : <string>,
  "format" : <string>, (optional)
  "meas" : <string>, (optional)
  "unit" : <string>, (optional)
  "desc" : <string>, (optional)
  "def" : <string>, (optional)
  "ref" : <string>, (optional)
  "key" : <boolean>, (optional, default false)
  "nul" : <boolean>, (optional, default false)
  "strict" : <boolean>, (optional, default false)
  "lock" : <boolean>, (optional, default false)
  "options" : [ <[#Field Option|field option]>, ... ] (optional)
}
```

Field Option

A value option for a field. Regardless of the field type the value here should be a string representation of the actual value.

```
{
  "value" : <string>,
```



```
"desc" : <string> (optional)
}
```

Blob

Defines a XINA database blob. The `name` is required. If `label` is not provided it will be the same as `name`.

```
{
  "name" : <string>,
  "label" : <string>, (optional)
  "desc" : <string>, (optional)
  "nul" : <boolean> (optional, default false)
}
```

Index

Defines an index on one or more columns of a database record table.

Action Index

ACCESS

Acquire temporary access ID for websocket connection.

ALTER

Edit schema or user properties.

APPROVE

Approve user requests.

CANCEL

Cancel one or more asynchronous tasks.

CLEAN

Delete one or more asynchronous task records and any associated files.

CONCLUDE

Explicitly conclude an asynchronous task.

CREATE

Create group, database, team, or user entities.

DELETE

Permanently delete one or more database records.

DESTROY

Cancel and clean one or more asynchronous tasks.

DISPOSE

Permanently delete one or more trashed database records.

DOWNLOAD

Acquire temporarily download links to one or more files.

DROP

Permanently delete a group, team, or database.

EDIT

Edit a wall post.

FETCH

Load a variety of data types in JSON friendly formats.

FOLLOW

Assign one or more walls to be followed by a user.

GRANT

Grant one or more users permissions on one or more groups or databases.

IF

Perform an action conditionally based on the result of a query.

INSERT

Insert one or more records into a database.

INSERT SELECT

Insert records into a database from an arbitrary query.

INVOKE

Invoke a synchronous AWS Lambda function.

JOIN

Join one or more users, groups, or databases to one or more teams.

KEY

Create or delete an API key for a user.

LEAVE

Remove one or more users, groups, or databases from one or more teams.

LINK

Create directional links from one or more records to one or more records.

LOAD

High performance record insertion using the MySQL LOAD DATA INFILE operation.

LOCK

Lock one or more records in a database.

MOVE

Rename an object in the general object store.

PAUSE

Pause execution of one or more asynchronous task threads.

POST

Send a post to a wall.

PREFER

Apply one or more preferences for a user.

PULL

Permanently delete a post from a wall.

REJECT

Deny a user request.

REPLACE

Insert one or more records into a database, replacing existing records with matching keys.

REPLACE SELECT

Insert records into a database from an arbitrary query, replacing existing records with matching keys.

REQUEST

Request an arbitrary action to be performed by a user with required permissions.

RESET

Resets a database to the initial state, permanently deleting all records.

RESTORE

Restores one or more trashed records to the active state.

RESUME

Resume execution of one or more asynchronous task threads.

RETRACT

Retract one or more user requests.

REVOKE

Revoke one or more permissions on one or more groups or databases from one or more users.

RUN

Run one or more asynchronous tasks.

SCHEMA

Returns the complete current group and database schema.

SELECT

Performs a SQL SELECT query.

SET

Inserts one or more records into a database, replacing all records already present in the database.

SIGN

Sign one or more records.

STORE

Add or remove data from the general object store.

STRUCT BUFFER DEPRECATE

Deprecates one or more mnemonic buffer files.

STRUCT BUFFER IMPORT

Import a single mnemonic buffer file.

STRUCT CREATE

Create struct schema elements.

STRUCT MN ALIAS

Adds one or more aliases to a struct mnemonic.

STRUCT MN EDIT

Edits system managed fields of a struct mnemonic.

STRUCT MN MERGE

Merges one or more struct mnemonics into a single mnemonic.

SUBSCRIBE

Subscribes one or more users to notifications from one or more walls.

TAG

Applies one or more tags to one or more records in a single database.

TEAMS

Returns the complete team schema.

TRASH

Trashes one or more records in a database.

UNFOLLOW

Remove one or more walls from being followed by one or more users.

UNLINK

Permanently delete links between records.

UNLOCK

Unlock one or more records in a database.

UNSIGN

Remove signature from a record.

UNSUBSCRIBE

Remove subscriptions from one or more walls for one or more users.

UNTAG

Remove one or more tags from one or more records in a single database.

UPDATE

Update the fields, blobs, or file of one or more records in a single database.

UPDATE EXPRESSION

Update the fields, blobs, or file of one or more records in a single database, supporting field values defined as arbitrary expressions.

VERSION

Returns the current XINA version information.

VIEW

Marks tasks or notifications as viewed by a user.

WAIT

Waits a specified period of time and returns.

XDOWNLOAD

Generates a XINA Download utility file for set of file downloads.