

Utilities

Detailed information on XINA utility applications.

- [XINA Connect](#)
- [XINA Tunnel](#)
- [XINA Import](#)
- [XINA Import Helper](#)
- [XINA Download](#)
- [XINA API Libraries](#)
- [XINA Struct Archive](#)
- [XINA Struct Mine](#)
- [XINA Struct Export](#)
- [XINA Struct Trend](#)
- [XINA Struct Report](#)
- [XINA Struct Report Email](#)

XINA Connect

XINA Connect is a Java application which combines the features of the XINA Tunnel and XINA Import applications with a UI. This application is distributed as a Java jar file and requires Java 17 or greater to run. The recommended OpenJDK build is available [here](#).

Latest Version

13.3.0

[Jar File](#) (requires Java 21+)

```
java -jar xina-connect.jar
```

Previous Versions

1.1.0

[Windows Installer](#)

[Windows Portable](#)

[MacOS Installer](#)

[Jar File](#) (requires Java 17+)

```
java -jar xina_connect.jar
```

1.0.0

[Windows Installer](#)

[MacOS Installer](#)

XINA Tunnel

XINA Tunnel is a command line application required for client applications to communicate with the XINA Server via the [XINA API](#). This application is distributed as a Java jar file and requires Java 21 or greater to run. The recommended OpenJDK build is available [here](#).

Latest Version

XINA Tunnel 13.3.0

[Download](#)

Usage

Windows

```
java -jar "path to xina_tunnel.jar" ^  
-host "host URL or IP address" ^  
-keyfile "path to key.json"
```

MacOS, Linux

```
java -jar "path to xina_tunnel.jar" \  
-host "host URL or IP address" \  
-keyfile "path to key.json"
```

Old Versions

XINA Tunnel 9.2.0

[Download](#)

Usage

Windows

```
java -jar "path to xina_tunnel.jar" ^  
-host "host URL or IP address" ^  
-keyfile "path to key.json"
```

MacOS, Linux

```
java -jar "path to xina_tunnel.jar" \  
-host "host URL or IP address" \  
-keyfile "path to key.json"
```

XINA Import

XINA Import is a utility for importing XINA API actions as JSON files. This application is distributed as a Java jar file and requires Java 21 or greater to run. The recommended OpenJDK build is available [here](#).

Latest Version

XINA Import 13.3.0

[Download](#)

Windows

```
java -jar "path to xina_import.jar" ^  
[additional arguments...]
```

MacOS, Linux

```
java -jar "path to xina_import.jar" \  
[additional arguments...]
```

| Argument | Info | Default |
|-------------------------------------|---|----------------------------|
| <code>-host <hostname></code> | the XINA Tunnel host | <code>"localhost"</code> |
| <code>-post <port></code> | the XINA Tunnel port | <code>41746</code> |
| <code>-okmove <path></code> | if set, move files to path to after successful import | none (files are not moved) |
| <code>-oktrash</code> | if set, move files to OS trash after successful import | <code>false</code> |
| <code>-okdelete</code> | if set, permanently delete files after successful import | <code>false</code> |
| <code>-ermove <path></code> | if set, move files to path to after failed import | none (errors stop import) |
| <code>-dir <path></code> | path to directory containing files to import | |
| <code>-watch <path></code> | path to directory to watch for files to import | |
| <code>-recursive</code> | if true in <code>dir</code> or <code>watch</code> mode, searches directory recursively for JSON files | <code>false</code> |

XINA Import has three modes of operation:

File List

JSON files can be listed explicitly. They will be imported in the specified order.

```
java -jar "path to xina_import.jar" \  
    "path to JSON file" \  
    "path to JSON file"...
```

Directory

If the `-dir` argument is used, XINA Import will attempt to import all `*.json` files in the specified directory in alphanumeric order.

Note: the directory is now queried after each imported file, so at one of `-okmove`, `-oktrash`, or `-okdelete` must be specified in this mode, or the same file would be imported repeatedly in an infinite loop.

```
java -jar "path to xina_import.jar" \  
    -dir "path to directory" \  
    -okmove "path to different directory"
```

Watch

If the `-watch` argument is used, XINA Import will attempt to import all `*.json` files in the specified directory in alphanumeric order. Once complete, the directory is watched for any new JSON files, which are imported as they become available. As with directory mode, a `-ok*` argument is required to prevent the same file from being imported repeatedly.

```
java -jar "path to xina_import.jar" \  
    -watch "path to directory" \  
    -okmove "path to different directory"
```

Previous Versions

XINA Import 10.1.0

[Download](#)

Windows

```
java -jar "path to xina_import.jar" ^  
[additional arguments...]
```

MacOS, Linux

```
java -jar "path to xina_import.jar" \  
[additional arguments...]
```

| Argument | Info | Default |
|----------|------|---------|
|----------|------|---------|

| | | |
|-------------------------------------|---|----------------------------|
| <code>-host <hostname></code> | the XINA Tunnel host | <code>"localhost"</code> |
| <code>-post <port></code> | the XINA Tunnel port | <code>41746</code> |
| <code>-okmove <path></code> | if set, move files to path to after successful import | none (files are not moved) |
| <code>-oktrash</code> | if set, move files to OS trash after successful import | <code>false</code> |
| <code>-okdelete</code> | if set, permanently delete files after successful import | <code>false</code> |
| <code>-ermove</code> | if set, move files to path to after failed import | none (errors stop import) |
| <code>-dir <path></code> | path to directory containing files to import | |
| <code>-watch <path></code> | path to directory to watch for files to import | |
| <code>-recursive</code> | if true in <code>dir</code> or <code>watch</code> mode, searches directory recursively for JSON files | <code>false</code> |

XINA Import has three modes of operation:

File List

JSON files can be listed explicitly. They will be imported in the specified order.

```
java -jar "path to xina_import.jar" \
    "path to JSON file" \
    "path to JSON file"...
```

Directory

If the `-dir` argument is used, XINA Import will attempt to import all `*.json` files in the specified directory in alphanumeric order.

Note: the directory is now queried after each imported file, so at one of `-okmove`, `-oktrash`, or `-okdelete` must be specified in this mode, or the same file would be imported repeatedly in an infinite loop.

```
java -jar "path to xina_import.jar" \
    -dir "path to directory" \
    -okmove "path to different directory"
```

Watch

If the `-watch` argument is used, XINA Import will attempt to import all `*.json` files in the specified directory in alphanumeric order. Once complete, the directory is watched for any new JSON files, which are imported as they become available. As with directory mode, a `-ok*` argument is required to prevent the same file from being imported repeatedly.

```
java -jar "path to xina_import.jar" \
    -watch "path to directory" \
```

-okmove "path to different directory"

XINA Import 9.2.0

[Download](#)

Usage

Windows

```
java -Dlog4j.configurationFile="path to log4j2.xml" ^  
-jar "path to xina_import.jar" ^  
[additional arguments...]
```

MacOS, Linux

```
java -Dlog4j.configurationFile="path to log4j2.xml" \  
-jar "path to xina_import.jar" \  
[additional arguments...]
```

| Argument | Info | Default |
|-------------------------------------|---|----------------------------|
| <code>-host <hostname></code> | the XINA Tunnel host | <code>"localhost"</code> |
| <code>-post <port></code> | the XINA Tunnel port | <code>41746</code> |
| <code>-movejson <path></code> | directory to move JSON files to after import | none (files are not moved) |
| <code>-movefile <path></code> | directory to move other files to after import | none (files are not moved) |
| <code>-deljson</code> | if set, permanently delete JSON files after import | <code>false</code> |
| <code>-delfile</code> | if set, permanently delete other files after import | <code>false</code> |
| <code>-dir <path></code> | path to directory containing files to import | |
| <code>-watch <path></code> | path to directory to watch for files to import | |
| <code>-recursive</code> | if true in <code>dir</code> or <code>watch</code> mode, searches directory recursively for JSON files | <code>false</code> |

XINA Import has three modes of operation:

File List

JSON files can be listed explicitly. They will be imported in the specified order.

```
java -jar "path to xina_import.jar" \  
"path to JSON file" \  
"path to JSON file"...
```


Directory

If the `-dir` argument is used, XINA Import will attempt to import all `*.json` files in the specified directory in alphabetical order. It is recommended to include `-movejson` or `-deljson` to track progress, in case the import is interrupted.

```
java -jar "path to xina_import.jar" \  
  -dir "path to directory" \  
  -movejson "path to different directory"
```

Watch

If the `-watch` argument is used, XINA Import will attempt to import all `*.json` files in the specified directory in alphabetical order. Once complete, the directory is watched for any new JSON files, which are imported as they become available. It is required to include `-movejson` or `-deljson`, as otherwise files would be continuously re-imported.

```
java -jar "path to xina_import.jar" \  
  -watch "path to directory" \  
  -movejson "path to different directory"
```

XINA Import Helper

XINA Import Helper is a utility for generating the XINA API actions as JSON files for an archive directory. The following XINA action files will be generated:

- Cancel any existing task(s) for the archive
- Delete the archive if it already exists in XINA
- Import the file archive
- Run the mining task on the archive to extract the data

The output files can then be imported into XINA using [XINA Import](#). This application is distributed as a Java jar file and requires Java 17 or greater to run. The recommended OpenJDK build is available [here](#).

Latest Version

XINA Import Helper 11.2.3

[Download](#)

Windows

```
java -jar "path to xina-import-helper.jar" ^  
[additional arguments...]
```

MacOS, Linux

```
java -jar "path to xina-import-helper.jar" \  
[additional arguments...]
```

XINA Download

XINA Download is a utility for managing batch file downloads with XINA. This application currently works with the SAM and MOMA XINA instances for telemetry file management only.

Latest Version

Windows Installer

[xina_download.exe](#)

MacOS Installer

[xina_download.dmg](#)

XINA API Libraries

We aim to provide a variety of reference XINA API client implementations for different programming languages and environments.

Python

[xina_api_python_0.4.0.zip](#)

Installation

Prerequisites

- Python 3.8 or greater

The `xina` client communicates with XINA via the [XINA Tunnel](#) utility. You must have it running for the `xina` client to connect.

Steps

1. Extract the zip file.
2. Open a terminal in the root extracted directory, and execute the following commands:

```
python3 -m pip install .
```

Examples

Client class

```
from xina import XPClient

with XPClient() as x:
    res = x.act({'action': 'version'})

print(res)

# => {'schema':100, 'host':'sandbox.xina.io', 'server':'9.1.4', 'team':100}
```

CLI

```
python -m xina action '{"action":"version"}'
```

```
# => {"schema":100,"host":"sandbox.xina.io","server":"9.1.4","team":100}
```

XINA Struct Archive

The XINA Struct Archive utility processes mnemonic buffer files into mnemonic archive files. It is primarily intended to be run as part of the automated XINA Structs data pipeline.

Arguments

| Name | Req | Description | Default |
|--------|-----|---|-------------|
| task | ? | task ID | |
| conf | ? | JSON conf file path | |
| temp | ? | temp directory path | |
| import | ? | import directory path (for file outputs) | |
| post | ? | post directory path (for post-import outputs) | |
| host | | tunnel host | "localhost" |
| port | | tunnel port | 41746 |

Configuration

| Name | Req | Description | Default |
|--------|-----|--------------------------------|---------|
| origin | ? | origin group | |
| slice | | slice length in minutes | 60 |
| t | | slice time barrier (see below) | |

Operation

This utility serves three main functions. First, processing raw buffer files of any supported format into well formatted, optimized xbin files. Second, merging buffer file data into time slice separated archive files. Third, processing any changes of flagged buffer files and updating associated archives as needed.

File Processing

Buffer files are typically imported in the `PENDING` state, and must be converted into xbin files, which are indicated with the `PROCESSED` state.

XINA Struct Mine

The XINA Struct Mine utility processes archive files to produce data products for import into XINA. It is primarily intended to be run as part of the XINA Structs data pipeline's Mining Task. There are 2 supported archive file formats: `xbin` and `xpf`. If the archive file is in the `xpf` format, processing is delegated to a mission specific tool.

See the [Struct Extract Interface](#) that describes the interface the tool shall implement.

Arguments

| Name | Req | Description | Default |
|--------|-----|---|-------------|
| task | ? | task ID | |
| conf | ? | JSON conf file path | |
| temp | ? | temp directory path | |
| import | ? | import directory path (for file outputs) | |
| post | ? | post directory path (for post-import outputs) | |
| host | | tunnel host | "localhost" |
| port | | tunnel port | 41746 |

Configuration

| Name | Req | Description | Default |
|---------------------------|-----|---|---------|
| pipe | ? | pipe group path, or model path if no pipe | |
| slice | | slice length in minutes | 60 |
| t | | TBD REMOVE slice time barrier (see below) | |
| TODO: Add re-mine options | | | |

Operation

This utility serves a few main functions:

- Extract data from archive files to produce import products such as:
 - Full mnemonic data
 - Delta mnemonic data
 - Time and Interval bin data
 - Filtered mnemonic data
 - Events (Actions?)
 - Limit Report

- Metrics
- Mission Specific Data

XINA Struct Export

The XINA Struct Export command line utility processes archive files for a specified time range to produce data products for XINA's Export Tasks. There are 2 supported archive file formats: `xbin` and `xpf`. If the archive file is in the `xpf` format, processing is delegated to a mission specific tool. See the [Struct Extract Interface](#) that describes the interface the tool must implement. Available data products include:

- Full resolution mnemonic data with a configurable format
- Mnemonic data statistics
- Configurable plots of data
- Limit Report
- Events
- Log file

Arguments

| Name | Req | Description | Default |
|--------------|-----|---|--------------------------|
| cache | | Cache directory path. Used for any persistent caching across tasks for optimization purposes. | |
| cancellation | | Path to the cancellation file for detecting cancel requests. | |
| conf | ? | File path to the JSON config containing the export parameters. | |
| env | ? | File path to the JSON environment file which defines environment parameters such as project specific paths. | |
| extract | | Overrides the path provided in the environment file to the struct_extract app. Only used if the archive format is <code>xpf</code> . | |
| help | | Print available options. | |
| host | | XINA Tunnel host. | <code>"localhost"</code> |
| port | | XINA Tunnel port. | <code>41746</code> |
| import | ? | Import directory path. Files that need to be imported will be placed here. <code>struct_export</code> is responsible for generating the corresponding import action file but <code>xina-run</code> will perform the actual importing. | |
| log | ? | File path that log events will be written to. | |

| Name | Req | Description | Default |
|------------|-----|---|---------|
| out | ? | Ouptut directory path. Files placed here will be uploaded and accessible directly from the Task interface (e.g. notifications panel). | |
| pkt_models | | Models to use packet time by default. [TBD Remove] | |
| plot | ? | Overrides the path provided in the environment file to the app that generates plot PDFs. | |
| post | ? | Post directory path (for post-import outputs) e.g. uploading log files to the Task record. | |
| python | ? | Overrides the path to the Python executable used by the plot app provided in the environment file. | |
| task | ? | File path to the JSON file containing info about the Task. | |
| temp | ? | Temp directory path for storing temporary files during execution. For example, zipped archives are unzipped to this directory for processing. | |

conf

The below table describes the available fields in the `conf` JSON file and is used to control how data should be exported.

| Name | Type | Req | Description | Default |
|-------|--------------------------|-----|--|---------|
| model | <code>utf8text</code> | ? | Path of model to export data from e.g. <code>moma.fm</code> | |
| start | <code>instant(us)</code> | ? | Start time of data to export. May be provided as a Unix timestamp in microseconds (e.g. <code>1738781947000000</code>) or an ISO 8601 formatted string (e.g. <code>2024-06-12T00:00:00Z</code>). | |
| end | <code>instant(us)</code> | ? | End time of data to export. May be provided as a Unix timestamp in microseconds (e.g. <code>1738781947000000</code>) or an ISO 8601 formatted string (e.g. <code>2024-06-12T00:00:00Z</code>). | |

| Name | Type | Req | Description | Default |
|----------------|------------------|-----|---|--|
| uuid | UUID | | Event UUID of interval if the export was requested for an interval. The event's start and end time will be used instead of <code>start</code> and <code>end</code> . | |
| disable_filter | boolean | | If <code>true</code> , does not apply the filters defined in <code>data_conf</code> . This is useful if you want to export an existing profile that has filters, but don't want to apply the filters. | false |
| copy | boolean | | If true, the zip file will be uploaded and available from the Task UI. | false |
| label | utf8text | | The text that will be used to name the files and final zip file. The format will be like <code>2024_06_12_00_00_00_2024_06_12_00_20_00_profile_label</code> | |
| profile | utf8text | | The name of the Profile if the export was generated from one. If provided, then the Profile's <code>plot_conf</code> and <code>data_conf</code> will be used. | |
| auto_conf | struct_auto_conf | | The <code>struct_auto_conf</code> that triggered the export. Only provided if the export was auto generated. | |
| plot_conf | struct_plot_conf | | The plot configuration used to generate the plot PDF. See plot format . An empty object i.e. <code>{}</code> can be provided to generate the default plot configuration. If not provided, then plots will not be generated. | One mnemonic per plot, one plot per page, sorted by <code>mn_id</code> in ascending order. |
| data_conf | struct_data_conf | | See struct_data_conf | |
| multi | boolean | | [TBD REMOVE - Not currently supported] Has extract process all archives at once. This was added for performance reasons since loading the mnem def is slow. | |

Example conf:

Note: The `plot_conf` was truncated for brevity.

This example performs an export with fields provided directly in the `conf` object.

```
{
  "model": "oci.fm",
  "label": "test",
  "start": 1718150400000000,
  "end": "2024-06-12T00:20:00Z",
  "ueid": null,
  "copy": true,
  "plot_conf": {
    "trend_series": [
      "avg"
    ],
    "pages": [
      {
        "plots": [
          {
            "title": "OCI Pri Power (15A)",
            "mnemonics": [
              "PSE.OM1.OCI_PRI_CURR"
            ]
          },
          {
            "series": [
              {
                "mnemonic": "oci.dau.ddc.FPGA.CcdOpMode",
                "plot_options": {
                  "color": "k"
                }
              }
            ]
          }
        ]
      }
    ]
  },
  "data_conf": {
    "limit": false,
    "ids": "@#[42316,42318-42322,43255,44243,45140,45187-45210,45233-45236,45238,45240,45241,45245,45247,45248,45259,45260,45265-
```

```
45268,45270,45272,45273,45277,45279,45280,45291,45292,45442,45444,45446,45448,45450,45452,45454,4
5460,45462,45472,45538,45540,45542,45544,45546,45548,45550,45556,45558,45568,51908,51910,64097,64
109,64111,64113,64115,66333,66341,66349,66357,66365,66373,66381,67536,67537,69019,69024-
69026,69031,69032,69729,77534,77570,77696]sci",
  "dis": false,
  "fill": false,
  "columns": {
    "ts_utc_iso": true
  },
  "join": true,
  "pkt": true
}
```

This example performs an export for an existing [Profile Definition](#). The `data_conf` and `plot_conf` objects will be retrieved from the `OPS_FLT_OCI_SDS` profile.

```
{
  "model": "oci.fm",
  "profile": "OPS_FLT_OCI_SDS",
  "label": "test",
  "start": 1718150400000000,
  "end": "2024-06-12T00:20:00Z",
  "ueid": null,
  "copy": true,
}
```

XINA Struct Trend

The XINA Struct Trend command line utility generates trend data products for a specified time range or Event Intervals. It is used by the XINA Trend Task. Generated data products include:

- Binned trend data
- Configurable trend plots
- Log file

Arguments

| Name | Req | Description | Default |
|--------|-----|--|-------------|
| cache | | Cache directory path. Used for any persistent caching across tasks for optimization purposes. | |
| conf | ? | File path to the JSON config containing the trend parameters. | |
| env | ? | File path to the JSON environment file which defines environment parameters such as project specific paths. | |
| help | | Print available options. | |
| host | | XINA Tunnel host. | "localhost" |
| port | | XINA Tunnel port. | 41746 |
| import | ? | Import directory path. Files that need to be imported will be placed here. <code>struct_trend</code> is responsible for generating the corresponding import action file but <code>xina-run</code> will perform the actual importing. | |
| log | ? | File path that log events will be written to. | |
| out | ? | Output directory path. Files placed here will be uploaded and accessible directly from the Task interface (e.g. notifications panel). | |
| post | ? | Post directory path (for post-import outputs) e.g. uploading log files to the Task record. | |
| task | ? | File path to the JSON file containing info about the Task. | |
| temp | ? | Temp directory path for storing temporary files during execution. | |

conf

The below table describes the available fields in the `conf` JSON file and is used to control how data should be trended.

| Name | Type | Req | Description | Default |
|------------|-------------------|-----|--|---------|
| model | utf8text | ? | Path of model to trend data from e.g. <code>moma.fm</code> | |
| copy | boolean | | If true, the zip file will be uploaded and available from the Task interface. | false |
| trend | utf8text | | The name of the Trend Definition to generate the trend for. If provided, then the <code>profiles</code> , <code>trend_conf</code> , and <code>plot_conf</code> will be loaded from it. | |
| label | utf8text | | The text that will be used to name the files and final zip file. The format will be like <code>2024_06_12_00_00_00_2024_06_12_00_20_00_profile_label</code> | |
| profiles | set(utf8string) | | Name of profile(s) to include in trend | |
| trend_conf | struct_trend_conf | | See struct_trend_conf | |
| plot_conf | jsonobject | | See trend plot conf | |

Example conf:

This example performs a trend export with fields provided directly in the conf object.

```
{
  "label": "Test_Trend_From_Conf",
  "desc": "This is a test trend. The Trend parameters are provided in the conf.",
  "model": "model.path",
  "copy": true,
  "profiles": [
    "TEST_PROFILE"
  ],
  "trend_conf": {
    "t": [
      {
        "start": "2024-11-01T00:00:00Z",
        "end": "2024-11-01T00:10:00Z"
```

```
    }  
  ],  
  "bin_minutes": 1,  
  "disable_filter": false,  
  "intervals": null  
},  
"plot_conf": {}  
}
```

In this example, the trend will be generated from an existing [Trend Definition](#) named `TEST_TREND`.

```
{  
  "trend": "TEST_TREND",  
  "model": "model.path",  
  "copy": true  
}
```


XINA Struct Report

The XINA Struct Report command line utility generates Export and Trend tasks for Profiles and Trend Definitions that are configured to auto generate. It can also optionally generate the XINA Report Email Task. The Export tasks will export the previous days data and the Trend tasks will use the time ranges or intervals as configured in the Trend Definition. The most common use case is to create the XINA Report Task (xina_struct_report) using XINA's internal cron system once per day.

Arguments

| Name | Req | Description | Default |
|--------|-----|---|-------------|
| cache | | Cache directory path. Used for any persistent caching across tasks for optimization purposes. | |
| conf | ? | File path to the JSON config containing the report parameters. | |
| env | ? | File path to the JSON environment file which defines environment parameters such as project specific paths. | |
| help | | Print available options. | |
| host | | XINA Tunnel host. | "localhost" |
| port | | XINA Tunnel port. | 41746 |
| import | ? | Import directory path. Files that need to be imported will be placed here. | |
| log | ? | File path that log events will be written to. | |
| out | ? | Ouptut directory path. Files placed here will be uploaded and accessible directly from the Task interface (e.g. notifications panel). | |
| post | ? | Post directory path (for post-import outputs) e.g. uploading log files to the Task record. | |
| task | ? | File path to the JSON file containing info about the Task. | |
| temp | ? | Temp directory path for storing temporary files during execution. | |

conf

The below table describes the available fields in the `conf` JSON file.

| Name | Type | Req | Description | Default |
|----------|----------|-----|---|---------|
| model | utf8text | ? | Path of model to generate Export and Trend tasks for e.g. "moma.fm" | |
| hostname | utf8text | ? | The hostname that will be used for creating the URLs to the Export and Trend packages in the email contents e.g. "moma.xina.io" | |
| email | boolean | | If true, the report email task will be generated | true |

Example conf:

```
{
  "model": "pace.ops_pace",
  "hostname": "pace.xina.io",
  "email": true
}
```

XINA Struct Report Email

The XINA Struct Report Email command line utility will find daily Export and Trend packages created for the previous day, determine which users are registered to be emailed, and then create an email containing direct links to the Export and Trend packages. Note that this utility creates an email task for each user; the actual emailing will be handled by an AWS Lambda task.

Arguments

| Name | Req | Description | Default |
|--------|-----|---|-------------|
| cache | | Cache directory path. Used for any persistent caching across tasks for optimization purposes. | |
| conf | ? | File path to the JSON config containing the report parameters. | |
| env | ? | File path to the JSON environment file which defines environment parameters such as project specific paths. | |
| help | | Print available options. | |
| host | | XINA Tunnel host. | "localhost" |
| port | | XINA Tunnel port. | 41746 |
| import | ? | Import directory path. Files that need to be imported will be placed here. | |
| log | ? | File path that log events will be written to. | |
| out | ? | Ouptut directory path. Files placed here will be uploaded and accessible directly from the Task interface (e.g. notifications panel). | |
| post | ? | Post directory path (for post-import outputs) e.g. uploading log files to the Task record. | |
| task | ? | File path to the JSON file containing info about the Task. | |
| temp | ? | Temp directory path for storing temporary files during execution. | |

conf

The below table describes the available fields in the `conf` JSON file.

| Name | Type | Req | Description | Default |
|----------|----------|-----|---|---------|
| model | utf8text | ? | Path of model to generate emails for e.g. "moma.fm" | |
| hostname | utf8text | ? | The hostname that will be used for creating the URLs to the Export and Trend packages in the email contents e.g. "moma.xina.io" | |

Example conf:

```
{
  "model": "pace.ops_pace",
  "hostname": "https://pace.xina.io"
}
```